

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER. .X ±0.25



| ISSUE NUMBER | |
|--------------|--|
| ORIGINAL | |

(1)






NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED



| POWER/CO-AX CONTACT RATING: | 30A (CURRENT) |
|--------------------------------|-----------------------|
| (IF PRESENT) | |
| SIGNAL CONTACT CURRENT RATING: | 5A PER CONTACT |
| SIGNAL CONTACT RESISTANCE: | 10mΩ MAX. |
| | |
| | |

.XX ±0.13 .XXX ±0.05


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

OPERATING TEMPERATURE:


5000MΩ min.

1000V AC rms

-55°C ~ 125°C



| | | | | SW REFERENCE NO.: 629 COMBO ASSEMBLY | | |
|-----------------|---|--|-------------------------|--------------------------------------|-------|--|
| | COMBINATION D-SUB | | DRAWN: C.B | DATE: JAN. 01/20 | 19 | |
| | | | CHECKED: | DATE: | | |
| | EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 | |
| | TORONTO, ONTARIO CANADA | SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE | DRAWING NUMBER: 629-21W | 1640-3NB | ISSUE | |
| YOUR CONNECTION | YOUR CONNECTION TO QUALITY & SERVICE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | PART NUMBER: 629-21W | 1640-3NB | 1 | | |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT

