ſ	т <u>О</u> т	ш		0	Φ	A	
4	Z						4
ω				LAYOUT SHOWN AS EXA	MPLE		3
	Keying Shown as example						
	CHARACTERISTICS	ctor dimension					
	-Standard : Based on MIL-DTL-38999 Series III Dim	Nominal					
	-Shell Material : Aluminium ØS -Shell Plating : Black Zinc Nickel VV THREAD -Insulator : Thermoplastic -Contacts : Copper Alloy	25 Max 31 Max 0 M15x1-6g		SOURIAU shall not be liable for any n due to a use of the Products which the Specifications issued by either of th (professional recommendation	n does not comply with ne Parties or by a third	1	
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum		L	Country FR	Jurisdiction & C Not List		2
	-Durability : 500 Mating cycles -Delivered without Souriau contacts		PN: 8D511Z22PNL				
	-Temperature Range -65°C to +175°C		A 18-10-2016	First Release			_
	-Salt Spray : 500 hours						
	-Mass : 14.19 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTO	MOD N ^e	
			TITLE	TITLE Aluminium Plug 8D series			
_	BASIC SERIES: 8D 5 - 11 Z 22 P N L SHELL TYPE : Plug with RFI Shielding - - 11 Z 22 P N L	Delivered W/O Contacts	SCALE -[-	General linear Tolerances:	NPRI	DS / PROJECT 859	_
	CONTACT TYPE : Standard Crimp Contact	ORIENTATION : N	SOURIAU This document is the property SOURIAU it must not be reproduced or			SOURIAU must not be reproduced or	
		CONTACT TYPE : PIN(500 Matings)	FORMAT			municated without permission	_
	PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 11-22	FORMAT A3	SOURIAU E		SHEET	
L	H G F	E		8D511Z22 C			
	H I G I F I			U I	В	A	

	T	۵	н г	m	D	0	
4		Contact Layout 22*					
3	Ctc A B C D	X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905					
						SOURIAU shall not be due to a use of the the Specifications issued (professional re	Products w d by either
2					A 18-10-201 ISS DATE	PN: 8	505112
					Designed By: TITLE SCALE NA	Date:	Alumi neral linear olerances: ±
					FORMAT		

G

Н

F

Е

A3

D

С

