	ت D	П	m	I	D	0
4 3	R 22.6 Max 0 to					
		Keying Shown as	example			
	CHARACTERISTICS-Standard : Based on NL-DTL-38999 Series III-Shell Material: Stainless Steel-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer		Connector dimension Dim Nominal A 38.1±0.3 B 23.82+0.1/-0.15 R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1 VV THREAD M18x1-6g			SOURIAU sha due to a us the Specificatio (profes
2	 -Contact Plating : Gold over copper Alloy 0.8μm minin -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +200°C -Salt Spray : 500 hours 	num			A 28-09-2016 ISS DATE Designed By:	First Release Latest modifica Dat
1	BASIC SERIES: 8D 7 - 13 SHELL TYPE : Jam nut Receptacle	S 04 A D	ORIEN CONTACT TYPE : PIN(50 CONTACT LAY0		TITLE SCALE NA SOURIAU	

G F

Н

С

D

 \checkmark

Е

			A		
					4
LAYOUT SHOWN AS EXAMPLE	0				3
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed PN: 8D713S04AD					
ation - by MOD N° te: CUSTOMER DRAWING					
General linear Tolerances: ±	Tolerances: 859				
W.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission SOURIAU DRG N° SHEET					
JUNIAU DINU N				1/2	
BA					

ſ	T G	П	т		0	Φ	A		,
	Contact Layout $\xrightarrow{\bullet}^{+\gamma}$ $\xrightarrow{\bullet}^{+\gamma}$ $\xrightarrow{\bullet}^{+}$			J.	Panel cutout				
4	Contacts (Insert arrangement 13-4) Contact position ID A + .000 (0.00) + .150 (3.81)					Ω			4
	B +.146 (3.71) +.035 (0.89) C +.000 (0.00) 083 (2.11) D 146 (3.71) +.035 (0.89) Shell Arrangement no. Number of contacts Size contacts Service rating Contact location Supersedes 13 -4 4 16 I All MS20051-4				Dim Nominal	¥			
ى ت					B 24.26+0/-0.2 ØC 25.65+0.25/-				3
	<u> </u>			[
1	•				SOURIAU shall not be liable due to a use of the Prod the Specifications issued by e (professional recom	ucts which does not co	mply with y a third party		
N					_	Country Jurisd FR	iction & Control List Not Listed		2
					PN: 8D713S04AD				
				A 28-09-2016	A 28-09-2016 First Release				
				ISS DATE Designed By:	Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	
				TITLE	TITLE Stainless Steel Receptacle 8D series				
				SCALE -	General Tolerar		NPRDS / PROJECT 859		-
				SOURIAU	NA ± DSS SOURIAU WWW.SOURIAU.COM This document is the proper SOURIAU it must not be reproduced communicated without perm			ed or	1
				FORMAT		RIAU DRG N°		SHEET	
		F		A3		13S04AD-C		2/2	
	H G I	F I	E	/ D	C	В	A		