

## C4CAWUC2680AA0J

C4C, Film, Metallized Polypropylene, Power, 0.068 uF, 5%, 630 VAC, 2000 VDC, 70°C

## FRONT VIEW

## General Information Series C4C Dielectric Metallized Polypropylene Style Axial RoHS Yes Lead Wire Leads AEC-Q200 No Component Weight 9.327 g Miscellaneous Polyester Tape & Resin Protection.

## **SIDE VIEW**



Click here for the 3D model.

Dimensions	
D	17.5mm NOM
L	33mm NOM
LL	40mm +/-5mm
F	1mm NOM

Specifications		
Capacitance	0.068 uF	
Capacitance Tolerance	5%	
Voltage AC	630 VAC	
Voltage DC	2000 VDC	
Temperature Range	-40/+85°C	
Rated Temperature	70°C	
Dissipation Factor	0.05%	
Max dV/dt	1150 V/us	
Resistance	16.3 mOhms (100kHz)	
Ripple Current	7 Amps (100kHz 70C), 78 Amps (Peak)	

Packaging Specifications		
Packaging	Bulk, Bag	
Packaging Quantity	150	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.