

**Material and Finish**

- Shell: Steel, Nickel plated
- Insulator: PBT thermoplastic with glass-fiber reinforcement, UL94V-0 rated, Color: Black
- Contact Material: Socket - Brass
- Contact Plating Options:
  - Standard: gold flash on mating end, tin on termination end, nickel underplate on entire contact
  - 15 Option: 15u" gold on mating end, tin on termination end, nickel underplate on entire contact
  - 30 Option: 30u" gold on mating end, tin on termination end, nickel underplate on entire contact

**Electrical Specifications**

- Rated Current: 2A
- Rated Voltage: 30V RMS
- Insulation Resistance: more than 1000 megohms at 500V DC
- Contact Resistance: 13 milliohms max.
- Dielectric Withstanding Voltage: 1000V for 1 minute
- Operating Temperature: -55°C to +105°C

Part Number	Contact Area Plating Finish
K85X-EA-9S-KJ	Gold Flash (standard)
K85X-EA-9S-KJ15	15u" Gold (15 option)
K85X-EA-9S-KJ30	30u" Gold (30 option)




Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	02/25/09	New Drawing	S. Vien	H. MA		
A2	12/31/17	ECO #17-030	G. Serrato	C. Furumasa	S. Vien	01/19/09

**K85X-EA-9S-KJ**

D-Sub, Vertical, Soldercup, RoHS Compliant

9 Pin Female, JS, Threaded Bushings



UNITS  
mm