


## **SBC2-221-411** Aliases (UPIN2221411000) KEMET, SBC2, Power, 220 uH, 10%, 4mm



General Informati	ion
Series	SBC2
Style	Through-Hole
Description	Radial Leaded, Ferrite Power Inductors
Features	DC-DC Converters, Nickel-Zinc (NiZn) Ferrite Core
RoHS	Yes
Lead	Wire Leads
Core	Ferrite
Miscellaneous	Pin Lead Terminal

Specifications				
Inductance	220 uH			
Inductance Tolerance	10%			
Temperature Range	-20/+105°C			
Shielded	No			
Current	0.41 Amps			
DC Resistance	0.87 Ohms			

Click here for the 3D model.

Dimensions	
D	7mm MAX
L	10.5mm MAX
S	4mm +/-0.5mm
LL	5.5mm +/-1mm
F	0.6mm NOM

De altre altre a	C	£::
Packaging	Snec	TICATIONS

Component Weight	900 mg
Packaging	Bulk
Packaging Quantity	8000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.