

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A		INITIAL	08MAY2015	DW	CW
B		ECR-15-013292	24SEP2015	DL	CW
C		ECR-21-105887	26JUL2021	BS	CW
D		ECR-22-150866	20SEP2022	DL	CW

NOTES:

- TECHNICAL CHARACTERISTICS:  
INSULATION MATERIAL: PC  
RATED VOLTAGE: 250 V  
RATED CURRENT: 10 A  
INSULATION RESISTANCE:  $\geq 400M\Omega$   
RATED IMPULSE VOLTAGE: 4 KV  
POLLUTION DEGREE: 3  
CONTACT RESISTANCE:  $\leq 5 m\Omega$   
FLAMMABILITY: UL94V-0  
MATING CYCLES: 500 CYCLES  
WIRE RANGE: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.  
(ORDER No. REFER TO DRAWING:T20200X20XX000)

4X M3 SCREW, RECOMMENDED  
TIGHTENING TORQUE 0.5Nm



M4 SCREW  
RECOMMENDED  
TIGHTENING TORQUE  
1.2Nm

注释:

- 技术参数:  
绝缘材料: PC  
额定电压: 250V  
额定电流: 10A  
绝缘电阻:  $\geq 400M\Omega$   
额定脉冲电压: 4 KV  
污染等级: 3  
接触电阻:  $\leq 5 m\Omega$   
阻燃等级: UL94V-0  
插拔次数: 500次  
接线范围: 0.14-2.5 mm<sup>2</sup> (26-14 AWG)  
接线类型: 冷压接
- 端子需要单独订购。  
(订货号参考图面: T20200X20XX000)

PANEL CUT FOR INSERTS FOR USE  
WITHOUT HOODS/ HOUSINGS

HDD-072-F 73-144	T2031442201-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	08MAY2015	David Wang	
		CHK	08MAY2015	Chris Wang	
		APVD	08MAY2015	Xiang Xu	
		PRODUCT SPEC	108-137043		
		APPLICATION SPEC	114-137043		
		WEIGHT	-		
MATERIAL		FINISH	-		
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:			
mm		0 PLC	±-		
		1 PLC	±-		
		2 PLC	±-		
		3 PLC	±-		
		4 PLC	±-		
		ANGLES	±-		
			±-		
Customer Drawing		SCALE	1:1	SHEET	1 OF 1
		RESTRICTED TO	-		
		REV	D		

HDD-072-F 73-144

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A300779 © T2031442201000

SCALE 1:1 SHEET 1 OF 1 REV D

1470-19 (3/13)