

Specification Sheet

Part Number: TAG11L-789



Laser printable white polyester has a smooth surface, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.

Laser Tag Label, 0.65" x .20", 480 Per Sheet, PET, White, 5000/pkg

Article Number 594-11789

Type TAG11L

Color White (WH)

Quantity Per pack

Product Description HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 789 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.

Short Description Laser Tag Label, 0.65" x .20", 480 Per Sheet, PET, White, 5000/pkg

Global Part Name	TAG11L-789-WH
Width W (Imperial)	0.65
Width W (Metric)	16.5
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.60
Thickness T (Metric)	64.0
Height H (Imperial)	0.2
Height H (Metric)	5.08
Material	Type 789, Polyester (789)
Material Shortcut	789
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)

Operating Temperature -40°F to +300°F (-40°C to +149°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3919905060

Labels per Column 48

Labels per Row 10