



483030A10M006

No Pole
3-4 Pole

cable type
#24/3-4 AWG
PVC YELLOW

cable length
006----.6 Meters
020----2 Meters

MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH IN/MM
1200870306	483030A10M006	1.97' +1.75" -0 [0.6M +44.5 -0]
1200870309	483030A10M010	3.28' +2.19" -0 [1.0M +55.6 -0]
1200870312	483030A10M020	6.56' +3.50" -0 [2.0M +88.9 -0]
1200870353	484030A10M010	3.28' +2.19" -0 [1.0M +55.6 -0]
1200870354	484030A10M020	6.56' +3.50" -0 [2.0M +88.9 -0]

SPECIFICATION DATA

COMPONENT	MATERIAL	FINISH
LABEL	MYLAR	BLACK/YELLOW
COUPLER	BRASS	NICKEL PLATED
CONTACT	COPPER ALLOY	Au OVER Ni
INSERT	PUR	BLACK
O-RING	VITON	RED
OVERMOLD	TPE	YELLOW
CABLE #24/3-4	PVC	YELLOW
VOLTAGE RATING:	3-4 POL:60V/AC 75V/DCV	
AMPERAGE RATING:	3A	
PROTECTION CLASS:	IP 68	
OPERATING TEMPERATURE:	-20°C / 105°C	
UL CERTIFICATIONS	UL listed, File #E152210	
CSA CERTIFICATIONS	CSA CERTIFIED, File LR6837	

REV	DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
			mm	INCH	IN/MM				
2	UPDATED FOR PART NUMBER MATRIX EC NO: IPG2014-0989 DRWN: GGUSTAFS 11/27/13 CHKD: BARDEN APPR: BWOODMAN 2010/02/05	▽ = 0 ◻ = 0	4 PLACES ±---	±---	DRAWN BY DATE REISSNER 2010/02/02		NTS	INCH	NC/MIC 3/4P F/MM XM AWG 24 PVC
			3 PLACES ±---	±.005	CHECKED BY DATE FP 2010/02/05				
			2 PLACES ±.13	±.010	APPROVED BY DATE FPACHER 2010/02/05				MOLEX INCORPORATED
			1 PLACE ±.25	±.020	MATERIAL NO. DOCUMENT NO.				
			ANGULAR ± .5 °		SEE TABLE				SHEET NO. 1 OF 1
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				