

# GMA.0B.045.DA

# SUMMARY

#### # Wires



Image is for illustrative purpose only

Series	0B	
Termination type	No contacts / Accessory	
IP rating	0	
AWG wire size	0.00 - 0.00	
Cable Ø	4.50 - 5.20 mm	
Status	active	

## Download

Request a quote Catalog

# **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model	GMA*: Bend relief Blue
Keying	No keying
Housing Material	Thermoplastic polyurethane elastomer (Elastollan 1185 A)
Variant	A : Blue
Weight	.43 g
Performance	

### Performance


Configuration Insulator Rated Current

### Others

Temp (min / max): -40°C / +80°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# DRAWINGS



No keying

### Dimensions

	А	L
mm.	4.5	24
in.	0,18	0,94

# **RECOMMENDED BY LEMO**

### Tools

#### Cables

120222		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.