



## Screw Terminal Blocks

### 2000/ 2 DS

terminal block, 2 pole, insulating material: PA, cross-section rating: 16.0 mm<sup>2</sup>, pin spacing: 14.50 mm, mounting hole diameter: 4.3 mm, wire protector (DS): yes, fixing: screw, voltage rating: 500 V, current rating: 76 A



### Order Info

reference number (ref.no.)	128302
PU	120
EAN	4028012106530

### Type

type	terminal block
number of poles	2 pole
clamping units per pole	1
colour	natural
cross-section rating	16.0 mm <sup>2</sup>
connection type	screw
wire protector (DS)	yes

### Technical Data

voltage rating	500 V
current rating	76 A
insulating material	PA
contact material	brass
core cross-section min.	0.5 mm <sup>2</sup>
core cross-section max.	10.0 mm <sup>2</sup>
flammability rating	V-2
min. ambient temperature	-40 °C
max. ambient temperature operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	10.0-10.5 mm
assembly contact screw	1,0x5,5 / ⚙ 2,0 Nm
mounting hole diameter	4.3 mm
pin spacing	14.50 mm
fixing	screw

## Approvals

<b>acc. to EN 60998</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>
<b>acc. to CSA</b>	<a href="#">Download PDF</a>

## Accessories

<b>2000 BZ/ 2</b>	191802
<b>ZEL 110</b>	196420