



Product: 6308UE ☑

Security & Sound, #18-10c, BC, CMP

Product Description

Security & Sound Cable, Plenum-CMP 10-18 AWG stranded bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Suitable Applications:		Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls				
Construction Details						
Conductor						
Element	Number o	f Element	Size	Stranding	Material	
Conductor(s)	10	1	8 AWG	7x26	BC - Bare Copper	
nsulation	Ma	iterial	Nom	. Thickness	Nom. Insulation Diameter	Color Code
Element					0.000 :- (4.0)	Black Bad White Course Brown Block Course Valley Brown
Conductor(s)	PVC - Poly Chloride	yvinyl	0.009	in (0.23 mm)	0.063 in (1.6 mm)	Black, Red, White, Green, Brown, Blue, Orange, Yellow, Purple,
Conductor(s)		yvinyl	0.009	in (0.23 mm)	0.063 in (1.6 mm)	Black, Red, Wnite, Green, Brown, Blue, Orange, Yellow, Purple,
Conductor(s)	Chloride	yvinyl Nom. Thick		in (0.23 mm) Nom. Diam		Black, Red, White, Green, Brown, Blue, Orange, Yellow, Purple,
Conductor(s) Outer Jacket	Chloride	Nom. Thick	iness	Nom. Diam	eter Ripcord	Black, Red, White, Green, Brown, Blue, Orange, Yellow, Purple,

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Max. Current
Conductor(s)	6.5 Ohm/1000ft	32.5 pF/ft (107 pF/m)	9.8 Amps per conductor @ 25°C

Voltage

UL Voltage Rating 300 V

Mechanical Characteristics

Temperature

UL Temperature	Operating
75°C	0°C to +75°C

Bend Radius

Stationary Min.	Installation Min	
2.8 in (71 mm)	2.8 in (71 mm)	

Max. Pull Tension:	224 lbs (102 kg)
Bulk Cable Weight:	71 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum), FT6, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5308UE

History

Update and Revision:	Revision Number: 0.424 Revision Date: 01-20-2023

Part Numbers

Variants

Item #	Color	UPC
6308UE 8771000	Natural	612825175629

© 2023 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.