





## 5.6

NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0 SHELL: STEEL, TIN PLATED CONTACT: COPPER ALLOY, 30µ GOLD PLATED OPERATING TEMPERATURE: -55°C to +105°C (1)

CURRENT RATING: 3A PER CONTACT CONTACT RESISTANCE: 25mΩ MAX. INSULATOR RESISTANCE: 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC rms

|  | SW REFERENCE NO.: 628 ASSEMBL          |  |                          | SSEMBLY          |       |
|--|--|--|--------------------------|------------------|-------|
|  | 628 SERIES D-SUB CONNECTOR             |  | DRAWN: C.B               | DATE: AUG. 01/20 | 018   |
|  |  |  | CHECKED:                 | DATE:            |       |
|  | EDAC INC<br>TORONTO, ONTARIO<br>CANADA | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: 1:1               | SHEET 1 OF       | 1     |
|  |  |  | DRAWING NUMBER: 628-025- | 620-261          | ISSUE |
|  | YOUR CONNECTION TO QUALITY & SERVICE   |  | PART NUMBER: 628-025-    | 620-261          | 1     |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.