-	<b>T</b>	Q	П	п	C	ז ו	O
4	R 22.6 Max	V Thread		S			LA
			Keying Shown as	s example			
N	-Durability: 500 Mating cycle-Delivered with Souriau contacts and Acce-Temperature Range: -65°C to +200°C	er er Alloy 0.8µm minimum es essories		Connector dimension           Dim         Nominal           A         38.1±0.3           B         23.82+0.1/-0.15           R         32.5Max           S         34.9±0.4           W         2.2+0.9/-0.1           VV THREAD         M18x1-6g		A 28-09-2016	SOURIAU shall due to a use the Specification (profess First Release
	-Salt Spray : 500 hours					ISS DATE	Latest modificat
_	BASIC SERIES: 8D SHELL TYPE : Jam nut Receptacle	7 13S	98 A C			Designed By: TITLE SCALE NA	Date:
	CONTACT TYPE : Standard Crimp Contac	ct				SOURIAU	WWW
	SHELL SIZE : 13 PLATING : S = Nickel			CONTACT TYPE : PIN(		FORMAT	
				CONTACT LA		A3	
L	Н	G	F	E	/ C	)	С

	Φ		A		
					4
LAYOUT SHOWN AS EXA	MPLE				3
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D713S98AC					2
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series					
General linear NPRDS / PROJECT Tolerances: <b>859</b> ± This document is the property of				perty of	1
W.SOURIAU.CC	it mus	SOURIAU t not be reproduc cated without pe	ed or		
8D713S98AC-C     1/2       B     A					]

	ت D			_		
	Contact Layout		Panel cutout			
4	$ \begin{array}{c}                                     $		JAM NUT RECEPTACLE (TYPE 7)	4		
	(Insert arrangement 13-98)           Location           Contact position ID         X-axis (mm)         Y-axis (mm)           A         +.000 (0.00)         +.195 (4.95)           B         +.125 (3.18)         +.150 (3.81)           C         +.193 (4.90)         +.030 (0.76)           D         +.104 (4.17)        105 (2.07)           E         +.000 (0.00)        135 (3.43)           F        164 (4.17)        105 (2.67)           G        193 (4.90)         +.030 (0.76)           H        125 (3.18)         +.150 (3.81)					
ω	J         +.065 (1.65)        015 (0.38)           K        065 (1.65)        015 (0.38)           Shell size         Arrangement no.         Number of contacts         Size contacts         Contact rating         Contact location           13         -98         10         20         I         All         MS20051-98		DimNominalB24.26+0/-0.25ØC25.65+0.25/-0	3		
			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
N			Country Jurisdiction & Control List FR Not Listed			
			PN: 8D713S98AC			
			A     28-09-2016     First Release     MOD N°       ISS     DATE     Latest modification - by     MOD N°       Designed By:     Date:     CUSTOMER DRAWING	-		
			TITLE Stainless Steel Receptacle 8D series			
<b></b>			SCALE     General linear     NPRDS / PROJECT       NA      Tolerances:     859	1		
			SOURIAU       This document is the property of         SOURIAU       SOURIAU         it must not be reproduced or         communicated without permission			
			FORMATSOURIAU DRG N°SHEETA38D713S98AC-C2/2			
L	H G	F E	D C B A	-		