

230V Automatic Voltage Switch with Surge Protection, 190 Joules, Direct Plug-In

MODEL NUMBER: AVS5D



Highlights

- Direct plug-in / 1 outlet
- Over- and undervoltage
 protection
- Surge and spike protection
- 5-amp current rating

Package Includes

- AVS5D Automatic Voltage Switch
- Owner's Manual

Description

AVS5D Automatic Voltage Switch is a power protection device combining overvoltage, undervoltage, lightning and spike/surge protection for your appliances and electronics. This device also guards against surges and spikes that may occur when power is restored. The AVS5D easily handles small refrigerators, small freezers, small air conditioners, TVs and computer equipment, plugged into its single outlet, from fluctuating power.

Program buttons let you quickly set voltage range, on/off delay, overload protection and digital display mode. The easy-to-read digital LED displays show you voltage, wattage, settings and status at a glance. The AVS5D features surge-protecting components to guard against spikes and surges.

Features

- 5-amp current rating
- BS 1363 UK plug
- BS 1363 UK outlet
- Program buttons
- Voltage LED
- Load LED
- Digital LED display

Specifications

OVERVIEW	
UPC Code	037332182197
OUTPUT	



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Output Receptacles (1 Right-Angle Outlets N INPUT Nominal Input Voltage(s) Supported 2 Recommended Electrical Service 2 Voltage Compatibility (VAC) 2 Maximum Surge Amps 4	50 / 60 Hz (1) British BS 1363A No 220V AC 230V
Right-Angle Outlets N INPUT INPUT Nominal Input Voltage(s) Supported 2 Recommended Electrical Service 2 Voltage Compatibility (VAC) 2 Maximum Surge Amps 4	No 220V AC 230V
INPUT Nominal Input Voltage(s) Supported 2 Recommended Electrical Service 2 Voltage Compatibility (VAC) 2 Maximum Surge Amps 4	220V AC 230V
Nominal Input Voltage(s) Supported 2 Recommended Electrical Service 2 Voltage Compatibility (VAC) 2 Maximum Surge Amps 4	230V
Recommended Electrical Service2Voltage Compatibility (VAC)2Maximum Surge Amps4	230V
Voltage Compatibility (VAC) 2 Maximum Surge Amps 4	
Maximum Surge Amps 4	
	230
Land Divertime	4500kA
Input Plug Type B	B\$1363
Input Cord Details D	Direct Plug-In
Input Cord Length (ft.) 0	
Right-Angle Plug N	No
Input Cord Length (m) 0	0.00
Integrated Cord Clip N	No
USER INTERFACE, ALERTS & CONTR	ROLS
Diagnostic LED(s) Y	Yes
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating 1	190
AC Suppression Response Time <	<1ns
Auto Shut-Off N	No
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection N	No
Cable (Coax) Protection N	No
Network (Ethernet) Protection N	No
PHYSICAL	
Anti-Microbial Protected N	No
Color L	Light Gray
Housing Color B	Black
Integrated Keyhole Mounting Slots N	No
Material of Construction P	Plastic
Receptacle Color V	White
Shipping Dimensions (hwd / cm) 1	13.49 x 8.59 x 6.60



Shipping Dimensions (hwd / in.)	5.31 x 3.38 x 2.60	
Shipping Weight (kg)	0.18	
Shipping Weight (lbs.)	0.40	
Unit Dimensions (hwd / cm)	13.21 x 6.40 x 4.78	
Unit Dimensions (hwd / in.)	5.20 x 2.52 x 1.88	
CERTIFICATIONS		
Certifications	CE	
Approvals	RoHS	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies