



General InformationSeriesL-RMSStyleSMD ChipDescriptionSurface Mount InductorRoHSYesCoreCeramic

Specifications	
Inductance	0.0091 uH
Inductance Tolerance	5%
Temperature Range	-55/+125°C
Current	150 mAmps (MAX)
DC Resistance	0.62 Ohms
Quality Factor	7 at 100 MHz, 17 at 800 MHz
Self-Resonant Frequency	3200 MHz MIN

Click	here	for	the	ЗD	model.
	i iei e	101	uie	$\mathcal{D}\mathcal{D}$	model.

Dimensions	
Chip Size	0201
L	0.6mm +/-0.03mm
W	0.3mm +/-0.03mm
Т	0.3mm +/-0.03mm
LL	0.15mm +/-0.05mm
В	0.15mm +/-0.05mm

Packaging Specifications	
Packaging	T&R
Packaging Quantity	15000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.