


40HV14N102KC

HV RAD-LDD Indust COG HVHT20OC, Ceramic, 1000 pF, 10%, 4000 VDC, COG, Commercial, High Temperature, HighVoltage, Lead Spacing = 12.7mm



Click here for the 3D model.

Dimensions	,
L	15.75mm MAX
Н	12.7mm MAX
Т	7.62mm MAX
S	12.7mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

Packaging Specifications			
Packaging	Waffle		
Packaging Quantity	20		

General Information			
Series	HV RAD-LDD Indust COG HVHT200C		
Style	Radial		
Description	Commercial, High Temperature, HighVoltage		
Features	Commercial		
RoHS	No		
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.		
SCIP Number	ef26097b-3862-4ee0-b0ad-404a563ece0f		
Termination	Copper		
Failure Rate	N/A		
AEC-Q200	No		

Specifications				
Capacitance	1000 pF			
Capacitance Tolerance	10%			
Voltage DC	4000 VDC			
Dielectric Withstanding Voltage	6000 VDC			
Temperature Range	-55/+200°C			
Temperature Coefficient	COG			
Dissipation Factor	0.15%			
Aging Rate	0% Loss/Decade Hour			
Insulation Resistance	100 GOhms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.