

PRODUCT DATASHEET CA12311_STRADA-SQ-T-DN

STRADA-SQ-T-DN

Beam for area lighting with shorter illumination distances. Assembly with installation tape.

SPECIFICATION:

Dimensions	25.0 x 25.0 mm
Height	8 mm
Fastening	tape, screw
ROHS compliant	yes 🛈



MATERIALS:

Component STRADA-SQ-T-DN ROSE-TAPE

Туре	
Single lens	
Таре	


Material	Colour	Finish
PMMA	clear	
Acrylic foam	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA12311_STRADA-SQ-T-DN	Single lens	2058	294	98	6.6
» Box size: 480 x 280 x 300 mm					



PRODUCT DATASHEET CA12311_STRADA-SQ-T-DN



See also our general installation guide: <u>www.ledil.com/installation_guide</u>

2/4



OPTICAL RESULTS (MEASURED):

CREE XM-L FWHM / FWTM Asymmetric Efficiency 92 % LEDs/each optic 1 Light colour White Required components: Image: Cree Component (Component (Componen	50*
LED XM-L FWHM / FWTM Asymmetric Efficiency 92 % LEDs/each optic 1 Light colour White Required components: CREE CIED LED XM-L2 FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/m LEDs/each optic 1	
FWHM / FWTM Asymmetric Efficiency 92 % LEDs/each optic 1 Light colour White Required components: ************************************	78
Efficiency 92 % LEDs/each optic 1 Light colour White Required components: ************************************	
Light colour White Required components:	601
Light colour White Required components: CREE CED LED XM-L2 FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/lm LEDs/each optic 1	
CREE LED LED XM-L2 FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/lm LEDs/each optic 1	
CREE LED XM-L2 FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/lm LEDs/each optic 1	\rightarrow
CREE LED XM-L2 FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/lm LEDs/each optic 1	
CREE LED XM-L2 FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/lm LEDs/each optic 1	
CREE LED XM-L2 FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/lm LEDs/each optic 1	30*
LED XM-L2 FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/lm LEDs/each optic 1	13.
FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/lm LEDs/each optic 1	90*
FWHM / FWTM Asymmetric Efficiency 92 % Peak intensity 0.5 cd/lm LEDs/each optic 1	
Peak intensity 0.5 cd/lm LEDs/each optic 1	1705
LEDs/each optic 1	50*
	60*
Light colour White	
Required components:	63*
	6.
20	6,
30*	G



PRODUCT DATASHEET CA12311_STRADA-SQ-T-DN

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc. 228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd. # 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy