

PRODUCT DATASHEET CA13892_MINNIE-XW

MINNIE-XW

 ${\sim}90^\circ$ extra wide beam optimized for LUXEON M/MX. Assembly with holder and installation tape.

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 35.0 mm
Height	15.8 mm
Fastening	tape
ROHS compliant	yes 🛈



MATERIAL SPECIFICATIONS:


Component	Туре	Material	Colour	Finish
MINNIE-XW	Reflector	HRPC	white	
MINNIE-HLD-M	Holder	PC	black	
SPUTNIK-TAPE	Таре	Acrylic foam	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA13892_MINNIE-XW	Reflector	840	120	60	6.4
» Box size: 476 x 273 x 292 mm					



PRODUCT DATASHEET CA13892_MINNIE-XW



See also our general installation guide: www.ledil.com/installation_guide



PHOTOMETRIC DATA (MEASURED):

CREE \$				90*		
LED	™ MHD-E/G					
FWHM / FWTM	89.0° / 140.0°			75*	\nearrow	K T
Efficiency	83 %				100	
Peak intensity	0.4 cd/lm			60.6		
LEDs/each optic	1				200	
Light colour	White			a.		
Required componer						
	10.				300	
					400	
				30'	15° 0°	15°
CREE \$	TM			90*		
LED	XHP70					V-1
FWHM / FWTM	91.0° / 144.0°			25*	100	
Efficiency	93 %			60*		
Peak intensity	0.4 cd/lm					
LEDs/each optic	1				200	
Light colour	White			97 (
Required componer	nts:				300	
					400	
				36*		
					15° 0°	15*
CREE \$	ты			90*		
LED	XHP70.2				\square	
FWHM / FWTM	90.0° / 135.0°			75%		
	00.0 / 100.0					
	87 %					
				60*		
Efficiency Peak intensity	87 %			50*	200	
Efficiency Peak intensity LEDs/each optic	87 % 0.4 cd/lm			45°	200	
Efficiency Peak intensity LEDs/each optic	87 % 0.4 cd/lm 1 White		Ν.	60*		
Efficiency Peak intensity LEDs/each optic Light colour Required componer	87 % 0.4 cd/lm 1 White hts:		R.	60*	200	
Efficiency Peak intensity LEDs/each optic Light colour Required componer	87 % 0.4 cd/lm 1 White					
Efficiency Peak intensity LEDs/each optic Light colour Required componer	87 % 0.4 cd/lm 1 White hts:		1	6.	200 	
Efficiency Peak intensity LEDs/each optic Light colour Required componer Protective	87 % 0.4 cd/lm 1 White nts: plate, glass			67	500	122
Efficiency Peak intensity LEDs/each optic Light colour Required componer Protective	87 % 0.4 cd/lm 1 White nts: plate, glass			60°	200 540 10 ¹	
Efficiency Peak intensity LEDs/each optic Light colour Required componer Protective	87 % 0.4 cd/lm 1 White nts: plate, glass			60° 60° 30°	209 	
Efficiency Peak intensity LEDs/each optic Light colour Required componer Protective	87 % 0.4 cd/lm 1 White nts: plate, glass XHP70.2 90.0° / 139.0°			60 67 39*	200 	
Efficiency Peak intensity LEDs/each optic Light colour Required componer Protective	87 % 0.4 cd/lm 1 White nts: plate, glass XHP70.2 90.0° / 139.0° 89 %			60 67 89 73 89	200	
Efficiency Peak intensity LEDs/each optic Light colour Required componer Protective	87 % 0.4 cd/lm 1 White hts: plate, glass XHP70.2 90.0° / 139.0° 89 % 0.4 cd/lm			60° 60° 30°	20	
Efficiency Peak intensity LEDs/each optic Light colour Required componer Protective CREEE LED FWHM / FWTM Efficiency Peak intensity LEDs/each optic	87 % 0.4 cd/lm 1 White hts: plate, glass XHP70.2 90.0° / 139.0° 89 % 0.4 cd/lm 1			60°	20	
Efficiency Peak intensity LEDs/each optic Light colour Required componen Protective	87 % 0.4 cd/lm 1 White hts: plate, glass XHP70.2 90.0° / 139.0° 89 % 0.4 cd/lm 1 White			60 10 10 10 10 10 10 10 10 10 1	200	
Efficiency Peak intensity LEDs/each optic Light colour Required componen Protective Protective	87 % 0.4 cd/lm 1 White hts: plate, glass XHP70.2 90.0° / 139.0° 89 % 0.4 cd/lm 1 White			60° 60° 30° 73° 60° 60°	200	
Efficiency Peak intensity LEDs/each optic Light colour Required componer Protective CREEE ¢ LED FWHM / FWTM Efficiency Peak intensity LEDs/each optic Light colour	87 % 0.4 cd/lm 1 White hts: plate, glass XHP70.2 90.0° / 139.0° 89 % 0.4 cd/lm 1 White			60° 60° 20° 20° 20°	20 	
Efficiency Peak intensity LEDs/each optic Light colour Required componer Protective CREEE ¢ LED FWHM / FWTM Efficiency Peak intensity LEDs/each optic Light colour	87 % 0.4 cd/lm 1 White hts: plate, glass XHP70.2 90.0° / 139.0° 89 % 0.4 cd/lm 1 White			60° 60° 30° 70° 60°	20 	



PHOTOMETRIC DATA (MEASURED):

	EDS	91 ³
LED	LUXEON M/MX	
FWHM / FWTM	90.0° / 133.0°	
Efficiency	92 %	
Peak intensity	0.5 cd/lm	
LEDs/each optic	1	
Light colour	White	
Required compone	ints:	30 ³ 23 ³ 6 ³ 33 ³
OSRAM Opto Semiconductors		90*
LED	OSCONIQ P 7070	75
FWHM / FWTM	130.0° / 94.0°	
Efficiency	%	
LEDs/each optic	1	
Light colour	White	er er
Required compone	ints:	



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc. 228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd. # 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy