


GT-2150R



General Information		
Series	GT	
Style	Metal Box	
Description	Noise Filters	
RoHS	With Exemptions	
SCIP Number	178c3d71-76e7-4e48-aa60-e3285a8f7efd	
Notes	DC Available.	
Miscellaneous	35 K Self-Temperature Rise Max.	
Lead	Screw Terminals	
Terminal Type	Screw	

Specifications		
Voltage AC	250 VAC	
Voltage	1500 VAC Withstanding Voltage 1 Min. Line to Ground	
Rated Current	15 A (AC/DC)	
Temperature Range	-25/+55°C	
Leakage Current	0.5 mA MAX (250 V 60 Hz)	
Resistance	300 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground	

Click here for the 3D model.

Dimensions	
L	84mm NOM
W	50.8mm NOM
Н	39mm NOM
Lead	Screw Terminals

Packaging Specifications		
Packaging	Tray, Box	
Packaging Quantity	20	
Component Weight	280 g	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Aliases (UNFGT2150RXXXX)

KEMET, GT, EMI/RFI Filters, Noise Suppression, 250 VAC