

ATGBICS Juniper JNP-QSFP-DAC-1M Compatible QSFP+ Direct Attach Copper Cable 40G QSFP+ 1m Passive

Brand : ATGBICS

Product code: JNP-QSFP-DAC-1M-C

Product name : Juniper JNP-QSFP-DAC-1M Compatible QSFP+ Direct Attach Copper Cable 40G QSFP+ 1m Passive

Juniper JNP-QSFP-DAC-1M Compatible QSFP+ Direct Attach Copper Cable 40G QSFP+ 1m Passive

ATGBICS Juniper JNP-QSFP-DAC-1M Compatible QSFP+ Direct Attach Copper Cable 40G QSFP+ 1m Passive:

ATGBICS JNP-QSFP-DAC-1M compatible 40GBase-CU QSFP+ to QSFP+ direct attach cable operates over passive copper with a cable length of 1m. It is suitable for short reach connection between two QSFP+ ports in 40G interconnecting networking applications. Our product is built to the exact specification of Juniper JNP-QSFP-DAC-1M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 40G InfiniBand 8x DDR, 4x QDR, IEEE 802.3ba 40Gigabit Ethernet, Fibre Channel, MSA QSFP+ SFF-8436 compliant.

ATGBICS Juniper JNP-QSFP-DAC-1M Compatible QSFP+ Direct Attach Copper Cable 40G QSFP+ 1m Passive. Cable length: 1 m, Connector 1: QSFP+, Connector 2: QSFP+, Data transfer rate: 40000 Mbit/s







Features		Features	
Product colour * Cable length *	able length *1 mable length *1 mconnector 1 *QSFP+connector 2 *QSFP+connector 1 gender *Maleconnector 2 gender *Malecket materialPolyvinyl chloride (PVC)conductor materialCopperchernet interface type40 Gigabit Ethernetetworking standardsIEEE 802.3ba	Plug and Play Certification	✓ CE,FCC
Connector 1 *		Operational conditions	
Connector 1 gender * Connector 2 gender * Jacket material Conductor material		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 70 °C -40 - 80 °C 10 - 90% 10 - 85%
Ethernet interface type		Packaging data	
Networking standards		Quantity per pack	1 pc(s)
AWG wire size		Technical details	
		Sustainability certificates	RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

×