

Specification Sheet

Part Number: 156-00589



2-Piece Cable Tie & Edge Clip, 8.0" Long, EC5A, 1–3 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg

| | |
|---------------------|--|
| Article Number | 156-00589 |
| Type | T50REC5A |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">•Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.•Edge Clip provides low insertion force and high extraction force ideal for assembly environments. |
| Quantity Per | bag |

Product Description

HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.

| | |
|--------------------------|--|
| Short Description | 2-Piece Cable Tie & Edge Clip, 8.0" Long, EC5A, 1–3 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg |
|--------------------------|--|

| | |
|-------------------------|--------------------------------|
| Global Part Name | T50REC5A-PA66UV/PA66HIRHSUV-BK |
|-------------------------|--------------------------------|

| | |
|--|------|
| Minimum Tensile Strength (Imperial) | 50.0 |
|--|------|

| | |
|--|-----|
| Minimum Tensile Strength (Metric) | 225 |
|--|-----|

| | |
|----------------------------|-----|
| Length L (Imperial) | 8.0 |
|----------------------------|-----|

| | |
|--------------------------|-------|
| Length L (Metric) | 202.0 |
|--------------------------|-------|

| | |
|------------------------|--|
| Fixation Method | EdgeClip, sideways, assembled, 2 piece |
|------------------------|--|

| | |
|--------------------------------------|------|
| Identification Plate Position | none |
|--------------------------------------|------|

| | |
|----------------|-----------------|
| Variant | Inside Serrated |
|----------------|-----------------|

| | |
|---------------------------|------|
| Width W (Imperial) | 0.18 |
|---------------------------|------|

| | |
|-------------------------|-----|
| Width W (Metric) | 4.6 |
|-------------------------|-----|

| | |
|---------------------------------------|------|
| Bundle Diameter Min (Imperial) | 0.20 |
|---------------------------------------|------|

| | |
|-------------------------------------|-----|
| Bundle Diameter Min (Metric) | 5.0 |
|-------------------------------------|-----|

| | |
|---------------------------------------|-----|
| Bundle Diameter Max (Imperial) | 2.0 |
|---------------------------------------|-----|

| | |
|-------------------------------------|------|
| Bundle Diameter Max (Metric) | 50.0 |
|-------------------------------------|------|

| | |
|-------------------------------|------|
| Thickness T (Imperial) | 0.05 |
|-------------------------------|------|

| | |
|---------------------------------------|---|
| Thickness T (Metric) | 1.2 |
| Height H (Imperial) | 0.61 |
| Height H (Metric) | 15.5 |
| Panel Thickness Min(Imperial) | 0.04 |
| Panel Thickness Max(Imperial) | 0.12 |
| Panel Thickness Min (Metric) | 1.0 |
| Panel Thickness Max (Metric) | 3.0 |
| Material | Polyamide 6.6 UV-stabilized (PA66UV) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66UV PA66HIRHSUV |
| Material Cable Tie | Polyamide 6.6 UV-resistant (PA66UV) |
| Flammability | UL 94 HB |
| Operating Temperature (Metric) | -40°F to +230°F (-40°C to +110°C) -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |

Customs Number

3926909988

Weight (Metric)

0.00281227

Weight (Imperial)

0.0062