



## RQT-PA



Aerosusa.com  
service@aerosusa.com  
855.393.9905

Plastic connector quick-type, T distributor for rational tubing assembly by just putting on, high density

Material: PA plastics

Temperature:

-40°C ... +120°C

-40°F ... +248°F

Protection Class: IP 68 | IP 69K

Color: Grey, Black

Properties:

- Rational tubing assembly due to one-piece screw connector with push-in lock for coarse and fine profile conduits
- Simple dismounting by displacing the snap-in sleeve
- Smallest outer dimensions to be used under confined conditions
- Free of silicone, cadmium and halogen
- Self-extinguishing
- Fit for high mechanical stress
- Impact-resistant

## CERTIFICATIONS



*"Unsurspassed in Cable Protection and Strain Relief"*

2409 Herr St.  
Harrisburg, PA 17103



Aerosusa.com  
service@aerosusa.com  
855.393.9905

## Technical Data Sheet

Product #	AD	B2 (in)	B1   3 (in)	C (in)	D (in)	E (in)	F (in)	lb/100	Color	PU
5020.041.208	OD1/OD3 - 15.8 / OD2 - 15.8	0.91	0.91	0.79	3.15	2.15	0.22	4.8502	Black	10 PC
5020.041.201	OD1/OD3 - 21.2 / OD2 - 21.2	1.16	1.16	1.06	3.68	2.6	0.26	9.0389	Black	10 PC
5020.041.202	OD1/OD3 - 28.5 / OD2 - 28.5	1.46	1.46	1.34	4.21	3.07	0.26	13.0073	Black	10 PC
5020.041.210	OD1/OD3 - 28.5 / OD2 - 34.5	1.73	1.73	1.5	4.45	3.03	0.26	15.2119	Black	10 PC
5020.041.211	OD1/OD3 - 34.5 / OD2 - 34.5	1.73	1.73	1.57	4.69	3.56	0.26	17.8574	Black	10 PC
5020.041.212	OD1/OD3 - 42.5 / OD2 - 42.5	2.05	2.05	1.77	5.43	3.72	0.26	25.7941	Black	10 PC
5020.041.213	OD1/OD3 - 54.5 / OD2 - 54.5	2.52	2.52	2.22	5.75	4.13	0.26	34.8330	Black	5 PC
5020.041.008	OD1/OD3 - 15.8 / OD2 - 15.8	0.91	0.91	0.79	3.15	2.15	0.22	4.8502	Grey	10 PC
5020.041.001	OD1/OD3 - 21.2 / OD2 - 21.2	1.16	1.16	1.06	3.68	2.6	0.26	9.0389	Grey	10 PC
5020.041.002	OD1/OD3 - 28.5 / OD2 - 28.5	1.46	1.46	1.34	4.21	3.07	0.26	13.0073	Grey	10 PC
5020.041.010	OD1/OD3 - 28.5 / OD2 - 34.5	1.73	1.73	1.5	4.45	3.03	0.26	15.2119	Grey	10 PC
5020.041.011	OD1/OD3 - 34.5 / OD2 - 34.5	1.73	1.73	1.57	4.69	3.56	0.26	17.8574	Grey	10 PC
5020.041.012	OD1/OD3 - 42.5 / OD2 - 42.5	2.05	2.05	1.77	5.43	3.72	0.26	25.7941	Grey	10 PC
5020.041.013	OD1/OD3 - 54.5 / OD2 - 54.5	2.52	2.52	2.22	5.75	4.13	0.26	34.8330	Grey	5 PC

*"Unsurpassed in Cable Protection and Strain Relief"*

2409 Herr St.  
Harrisburg, PA 17103