

THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.




5.80

10.70

Ν	Ю	Т	E	S	1

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC P STEEL, TIN PLATED COPPER ALLOY, 30	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	10A (CURRENT)	
SIGNAL CONTACT CURRENT RATING		
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.	
INSULATOR RESISTANCE:	5000MΩ min.	
DIELECTRIC		
WITHSTANDING VOLTAGE:	1000V AC rms	

	COMBINATION D-SUB			SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINA				19			
				DATE:			
	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC. AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2			
TORONTO, ON CANADA	OR USED AS THE BASIS FOR THE	DRAWING NUMBER: 630-2W2	-650-1TE	ISSUE			
YOUR CONNECTION TO QUALITY & SER	VICE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 630-2W2	-650-1TE	1			



ĦS F COMPLIANT

