







Multi-Level Fuse Blocks, 5 x 20mm + Feed Through + Ground

### CYDLGF4

### CYDLGF4L6-60V

### CYDLGF4L110-240V



Top: Fuse Block, 5x20mm  
Mid: Feed Through Terminal  
Bottom: Ground  
2x2 Jumper Channels

Top: Fuse Block, 5x20mm, LED  
Mid: Feed Through Terminal  
Bottom: Ground  
2x2 Jumper Channels

Top: Fuse Block, 5x20mm, LED  
Mid: Feed Through Terminal  
Bottom: Ground  
2x2 Jumper Channels

### Dimensions & Weight

Width	6 mm	6 mm	6 mm
Length	94.5 mm	94.5 mm	94.5 mm
Height w DIN Rail	35 x 7.5 mm 35 x 15 mm	90.9 mm 98.4 mm	90.9 mm 98.4 mm
Weight per piece	40.8 g	35.4 g	35.4 g

### Technical Data/Ratings

Approvals						
Wire Size (solid / stranded)	24-10 AWG	0.2-4 mm <sup>2</sup>	24-10 AWG	0.2-4 mm <sup>2</sup>	24-10 AWG	0.2-4 mm <sup>2</sup>
Voltage Rating	300 V	1000V AC/DC	300 V	1000V AC/DC	300 V	500V AC/DC
Current Rating Fuse (Top)	10 A	10 A	10 A	10 A	10 A	10 A
Current Rating Feed Thru (Mid)	30 A	30 A	30 A	30 A	30 A	30 A
Torque	4.5 lb-in	0.5 Nm	4.5 lb-in	0.5 Nm	4.5 lb-in	0.5 Nm
Insulation Material	Polyamide 66		Polyamide 66		Polyamide 66	

### Fuse Specifications

Fuse Type	5x20 / 5x25 mm	5x20 / 5x25 mm	5x20 / 5x25 mm
LED Indicator Voltage	-	6-60V AC/DC	110-240V AC/DC

### Installation Instructions

Wire Stripping Length	9 mm	9 mm	9 mm
Screwdriver	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm

### Terminal Blocks

<b>Grey (standard)</b>	<b>CYDLGF4</b>	Cat. No.	Std. Pk.	<b>CYDLGF4L6-60L</b>	Cat. No.	Std. Pk.	<b>CYDLGF4L110-240V</b>	Cat. No.	Std. Pk.
Blue BU	CYDLGF4/BU		50	CYDLGF4L6-60L/BU		50	CYDLGF4L110-240V/BU		50
Black BL	CYDLGF4/BL		50	CYDLGF4L6-60L/BL		50	CYDLGF4L110-240V/BL		50

Additional colors available.



### Accessories

DIN Rail		Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
		2511120	20	2511120	20	2511120	20
		CA701-15/S	20	CA701-15/S	20	CA701-15/S	20
End Stop		CA702	50	CA702	50	CA702	50
		CA802	50	CA802	50	CA802	50
		CA202	50	CA202	50	CA202	50
Shorting Link/Jumpers		JX4/2	100	JX4/2	100	JX4/2	100
		JX4/3	50	JX4/3	50	JX4/3	50
		JX4/4	50	JX4/4	50	JX4/4	50
		5 pole	-	-	-	-	-
		6 pole	-	-	-	-	-
		7 pole	-	-	-	-	-
		8 pole	JX4/8	JX4/8	10	JX4/8	10
		10 pole	JX4/10	JX4/10	10	JX4/10	10
		16 pole	JX4/16	JX4/16	10	JX4/16	10
Marking Tag		MT6	1 Pk. (100 tags)	MT6	1 Pk. (100 tags)	MT6	1 Pk. (100 tags)
Warning Label		WLX4	1 Pk. (100 tags)	WLX4	1 Pk. (100 tags)	WLX4	1 Pk. (100 tags)

### HIGHLIGHTS

- #### FEATURES
- Top Level fuse link for 5x20mm fuse types
  - Middle Level Feed-Through
  - Bottom Level Grounding Terminal
  - 6mm wide compact design
  - 2 internal jumper channels on each level
  - CYDLF4L version with LED for blown fuse indication
  - Blocks can be used in AC & DC applications

### APPLICATIONS

- Tight Space Fuse applications
- No need for additional Feed-Through Terminal
- Control Systems with fuse applications