



Plug-in miniature power relay, Encapsulated design with power contact, 2 CO contact, Input voltage: 12 VDC

Business data

6482.2
PRS 2/12V DC
4044211074210
1
PC
12.9 g
14.71 g
G
85364900
AT
Relay, encapsulated construction





Technical data	
Dimensions	
Length	29 mm
Width	12.7 mm
Height	15.7 mm
Ratings	
Overvoltage category	III
Contamination degree	3 (250 VAC) / 2 (400 VAC)
Input data	
Working voltage	>8,4 VDC -
Drop-out voltage	1,2 VDC
Coil voltage	12 VDC -
Power consumption	0,4 W
Coil resistance	360 Ohm
Output data	
Switching voltage / switching voltage max.	250 / 400 VAC
Continuous current max. / Inrush current max.	8 / 15 A
Contact configuration	2 CO contacts
Switching capacity, max.	2000 VA
Electrical lifespan (AC1)	1x10?
Mechanical lifespan	30x10?
Bounce time at close of the NO/NC contact	8/6 ms
Materials	
Contact material	AgNi 90/10
Working temperature, min.	-40 °C
Working temperature, max.	70 °C
Further technical data	
Degree of protection	RTII
Insulation voltage coil/contact	5 kV
Response/release time	8 / 6 ms
Insulation voltage contact/contact	1 kV
Vibration resistance NO/NC	20/5 g
Pinning	5 mm





Technical data		
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2022-01-07	
REACH Candidate Substance Note	No	
RoHS Conform	yes	





Approvals		
Standards and regulations		
CE compliant	yes	

Data sheet 6482.2 PRS 2/12V DC



Media

6482.2 PRS 2/12V DC



Accessories

##INVERSE##CONTA-ELECTRONICS



Relay socket base PRS, for miniature power relay with 2 CO contacts, Screw connection, Plug-in option for input/suppression modules, Mounting type: Mounting rail TS 35

Article number	Article name	GTIN (EAN)	Packaging unit
15136.2	PRS 2	4044211046194	1 ST



Relay socket base PRS, for miniature power relay with 2 CO contacts, Screw connection, Plug-in option for input/suppression modules, Mounting type: Mounting rail TS 35

Article number	Article name	GTIN (EAN)	Packaging unit
15320.2	PRS 2 G	4044211047115	1 ST



Relay socket base PRS, for miniature power relay with 2 CO contacts, Tension-spring connection, Plug-in option for input/suppression modules, Mounting type: Mounting rail TS 35

Article number	Article name	GTIN (EAN)	Packaging unit
15789.2	PRS 2 Z	4044211135256	1 ST



Pre-assembled relay module PRS..., Tension-spring connection, Consisting of: relay socket base, power contact relay, pluggable display/suppression module and holding clip, 2 CO contact, Input voltage: 12 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
15790.2	PRSU 2Z/12V DC	4044211135348	10 ST



Pre-assembled relay module PRS..., Screw connection, Consisting of: relay socket base, power contact relay, pluggable display/suppression module and holding clip, 2 CO contacts, Input voltage: 12 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15165.2</u>	PRSU 2/12V DC	4044211046446	10 ST



Pre-assembled relay module PRS..., Screw connection, Consisting of: relay socket base, power contact relay, pluggable display/suppression module and holding clip, 2 CO contacts, Input voltage: 12 VDC

Article number	Article name	GTIN (EAN)	Packaging unit
15414.2	PRSU 2G/12V DC	4044211080808	1 ST



##INVERSE##CONTA-ELECTRONICS



Plug-Relay-Compact (PRC) socket base PRC with screw connection, Mounting type: Mounting rail TS 35, 2 CO contact, Input voltage: 6.12 or 24 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15920.2	PRC 2 6-12-24V AC/DC	4044211137359	10 ST



Plug-Relay-Compact (PRC) socket base PRC with tension-spring connection, Mounting type: Mounting rail TS 35, 2 CO contact, Input voltage: 6, 12 or 24 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
<u>15922.2</u>	ZPRC 2 6-12-24V AC/DC	4044211137373	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with tension-spring connection and pluggable miniature relay PRS... with power contact, Mounting type: Mounting rail TS 35, 2 CO contacts, Input voltage: 12 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15927.2	ZPRCU 2 12V AC/DC	4044211137458	10 ST



Plug-Relay-Compact (PRC) Complete, Consisting of base PRC... with screw connection and pluggable miniature relay PRS... with power contact, Mounting type: Mounting rail TS 35, 2 CO contacts, Input voltage: 12 VAC/DC

Article number	Article name	GTIN (EAN)	Packaging unit
15924.2	PRCU 2 12V AC/DC	4044211137427	10 ST



Relay socket base PRS, for miniature power relay with 2 CO contacts, Push-in connection, Plug-in option for input/suppression modules and cross connections, Mounting type: Mounting rail TS 35

Article number	Article name	GTIN (EAN)	Packaging unit
<u>16503.2</u>	PPRS 2	4044211236298	20 ST