

## Specification Sheet

Part Number: 308-30421



Heat Shrink Tubing, HIS-3-Bag, 3:1 Shrink Ratio, 3/16", 4.8/1.5 Dia, PO, Clear, 10/pkg

**Article Number**

308-30421

**Type**

HIS-3-BAG 4.5/1.5 CL

**Color**

Clear (CL)

**Features & Benefits**

- Thin wall, flexible 3 to 1 shrink ratio material accommodates a wide range of component shapes and diameters.
- Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing).
- Polyolefin material provides excellent insulation and mechanical strength with good resistance to solvents, oils and fuels.
- Available in bulk reels, sticks and convenience bags (HIS-3 bags), for small to large volume applications.

**Quantity Per**

bag

**Product Description**

TFN31 series heat shrink tubing features a flexible, thin wall and highly flame retardant polyolefin material with a higher operating temperature range than general-use heat shrink tubing. and offers good resistance to solvents, oils and fuels. The 3 to 1 shrink ratio accommodates a variety of component shapes and sizes. TFN31 tubing is available in bulk reels, sticks and convenience bags (HIS-3 bags), for projects of all sizes.

**Short Description**

Heat Shrink Tubing, HIS-3-Bag, 3:1 Shrink Ratio, 3/16", 4.8/1.5 Dia, PO, Clear, 10/pkg

**Global Part Name**

HIS-3-BAG 4.5/1.5 CL-PO-X-CL

**Length L (Metric)**

200

**Variant**

Thin-Wall

**Nominal Diameter (Imperial)**

3/16

**Nominal Diameter (Metric)**

4.5

**Wall Thickness WT (Imperial)**

.024

**Wall Thickness WT (Metric)**

.60

**Material**

Polyolefin, cross-linked (PO-X)

**Material Shortcut**

PO-X

**Flammability**

UL 224 VW-1 (except clear)

**Operating Temperature (Metric)**

-67°F to +275°F (-55°C to +135°C)

<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	SAE - AMS - DTL-23053/5 Class 2 (clear) UL   ANSI/UL 224 SAE - AMS - DTL-23053/5 Class 1 and 3
<b>Package Quantity(Imperial)</b>	10
<b>Package Quantity (Metric)</b>	10
<b>Customs Number</b>	3926909987