Product data sheet Characteristics

DL1BKB3

Flashing LED, 24 Vac/Vdc Green





Main

Range Compatibility	Harmony XVD Harmony XVP Harmony XVB
Accessory / separate part designation	Protected LED bulb
Accessory / Separate Part Type	LED bulb
Accessory / separate part category	Lighting accessories
Accessory / separate part destination	Beacon and indicator bank
[Us] rated supply voltage	24 V AC/DC
Signalling type	Flashing
Signalling colour	Green
Sale per indivisible quantity	1

Complementary

Current Consumption	47 mA
Bulb base	BA 15d
Net Weight	0.03 lb(US) (0.015 kg)

Ordering and shipping details

Cracing and cripping actains	
Category	22611 - XVB-STACKLIGHTS
Discount Schedule	XV
GTIN	3389110967562
Nbr. of units in pkg.	1
Package weight(Lbs)	0.42 oz (12 g)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.38 in (3.5 cm)	
Package 1 width	1.77 in (4.5 cm)	
Package 1 Length	2.36 in (6 cm)	
Unit Type of Package 2	S01	
Number of Units in Package 2	60	
Package 2 Weight	32.91 oz (933 g)	
Package 2 Height	5.91 in (15 cm)	
Package 2 width	5.91 in (15 cm)	
Package 2 Length	15.75 in (40 cm)	

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

18 months