








**ISSUE NUMBER** (1)







## NOTES:

WITHSTANDING VOLTAGE:

.XX


±0.13

.XXX ±0.05

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC PC STEEL, TIN PLATED COPPER ALLOY, 30µ	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	50Ω (IMPEDANCE)	
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT	
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.	
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.	

1000V AC rms

SW REFERENCE NO .: 630 COMBO ASSEMBLY COMBINATION D-SUB DATE: JAN. 01/2019 DRAWN: C.B CHECKED: DATE: THESE DRAWINGS AND SPECIFICATIONS OF 2 SCALE: (IN C.A.D. 1:1) SHEET 1 EDAC INC ARE THE PROPERTY OF EDAC INC. AND TORONTO, ONTARIO SHALL NOT BE REPRODUCED, OR COPIED 630-5W5-640-5T6 ISSUE DRAWING NUMBER: OR USED AS THE BASIS FOR THE CANADA MANUFACTURE OR SALE OF APPARATUS 1 YOUR CONNECTION TO QUALITY & SERVICE PART NUMBER: 630-5W5-640-5T6 WITHOUT WRITTEN PERMISSION.



THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES

2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT

