


75HV34N102MC

HV RAD-LDD Indust COG HV, Ceramic, 1000 pF, 20%, 7500 VDC, COG, Commercial, High Voltage, Lead Spacing = 27.76mm



Click here for the 3D model.

Dimensions	
L	26.67mm MAX
Н	12.7mm MAX
Т	6.89mm MAX
S	27.76mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

Packaging Specifications

5 5 1	
Packaging	Waffle
Packaging Quantity	4

General Information			
Series	HV RAD-LDD Indust COG HV		
Style	Radial		
Description	Commercial, High Voltage		
Features	Commercial		
RoHS	No		
Prop 65	A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.		
SCIP Number	ef26097b-3862-4ee0-b0ad-404a563ece0f		
Termination	Copper		
Failure Rate	N/A		
AEC-Q200	No		

Specifications			
Capacitance	1000 pF		
Capacitance Tolerance	20%		
Voltage DC	7500 VDC		
Dielectric Withstanding Voltage	9000 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	COG		
Dissipation Factor	0.15%		
Aging Rate	0% Loss/Decade Hour		
Insulation Resistance	100 GOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.