

Han-Eco 16B-HSE-for DL-M25-glanded



Part number	19 43 116 0526			
Specification	Han-Eco 16B-HSE-for DL-M25-glanded			
HARTING eCatalogue	https://b2b.harting.com/19431160526			
Identification				
Category	Hoods/Housings			
Series of hoods/housingsHan-Eco® B				
Type of hood/housing	Hoods			
Description of hood/ housing	With integrated cable gland			

Version

Locking type	Double locking lever
Size	16 B
Version	Side entry
Cable entry	1x M25

Technical characteristics

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP66
Clamping range	9 17 mm

Material properties

Material (hood/housing)	Polyamide Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material flammability class acc. to UL 94	V-0

Specifications and approvals

Specifications	IEC 61984	
	EN 45545-2 R22: HL1, HL2, HL3	
	EN 45545-2 R23: HL1, HL2, HL3	
	EN 45545-2 R24: HL1, HL2, HL3	
Commercial data		

Packaging size

Page 1 / 2 | Creation date 2018-12-07 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

1



Commercial data

Country of origin

European customs tariff number

Germany 85389099