<u>م</u> ا	m	D	0			
			LAYOUT SHOWN AS EXAM	PLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium	DimNominalØS25 Max	[
-Shell Plating : Nickel	Z 31 Max VV THREAD M15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with			
-Insulator : Thermoplastic			the Specifications issued by either of the Parties or by a third party			
-Contacts : Copper Alloy			(professional recommendation,	technical notice.)		
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List		
-Contact Plating : Gold over copper Alloy 0.8μm minimum		[FR	Not Listed		
-Durability : 500 Mating cycles			PN: 8D511F22	2SB		
-Delivered with Souriau contacts and Accessories						
-Temperature Range : -65°C to +200°C		A 15-10-2016	First Release			
-Salt Spray : 48 hours - Mass : 16.89 g ± 10%		ISS DATE	Latest modification - by		MOD N°	
10.05 g ± 10/0		Designed By:	Date:	CUSTOMER DRAWING		
	TITLE	Aluminium Plug 8D series				
		SCALE	General linear	NPRDS / PROJECT		
BASIC SERIES: 8D 5 - 11 F 22	2 S B	-	Tolerances:	859		
SHELL TYPE : Plug with RFI Shielding		NA		This document is the proper	rty of	
CONTACT TYPE : Standard Crimp Contact	ORIENTAT	SOURIAU	WWW.SOURIAU.CON	COUDIALI		
SHELL SIZE : 11	CONTACT TYPE : SOCKET(500 N			communicated without perm		
PLATING : F = Nickel	CONTACT LAYOUT		SOURIAU DI	RG N°	SHEET	
		A3	8D511F225	SB-C	1/2	

	т	۵	٣	m		0	
4	(Contact Layout 22*					
ω	Ctc A B C D	11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905					
						SOURIAU shall not be due to a use of the the Specifications issued (professional re	Products v d by either ecommend
N					A 15-10-201 ISS DATE	6 First Release	Coun FR 8D511
					ISS DATE Designed By: TITLE SCALE NA	Date:	Alumi eneral linear folerances: ±
					FORMAT		URIAU. DURIAL

G

Н

F

Е

A3

D

С

