

1

2

3

4

5

6

7

A

A

B

B

C

C

D

D

E

E

F

F

G

G

H

H

① PIN ASSIGNMENT

P1	1	P2	1
1	2	1	2
2	3	2	3
3	4	3	4
4	5	4	5
5	6	5	6
6	7	6	7
7	8	7	8
8	9	8	9
9	10	9	10
10	11	10	11
11	12	11	12
12	13	12	13
13	14	13	14
14	15	14	15
15	16	15	16
16	17	16	17
17	18	17	18
18	19	18	19
19	20	19	20
20	21	20	21
21	22	21	22
22	23	22	23
23	24	23	24
24	25	24	25
25		25	
SHIELD		SHIELD	

PE BAG Packing

Electrical test:

- 100% short ,open,miswire test
- Conduct resistance: 5Ω max.
- Insulation resistance: 10MΩ min.
- Hi-Pot: DC 300V

④	COPPER FOIL	2	COPPER FOIL W32mm*L100mm
②	TIE	2	WHITE L=120mm
⑦	PE BAG	1	CLEAR SIZE: 210*280*0.05mm PRINT BLA
⑥	TUBE	2	HEAT SHRINK TUBE BLACK OD1.5*2
⑤	SCREW	4	#4-40UNC TYPE L=30mm,NICKEL
④	IN JACKET	18g	CLEAR LD-PE
	OUT JACKET	60g	BEIGE(IV-29) 40P PVC
③	CONN	1	DB 25P FEMALE SODER TYPE PIN
②	CONN	1	DB 25P MALE SODER TYPE PIN G
①	CABLE	1	UL20276 28AWG*18P+D(26AWG TC JACKET-BEIGE(IV-29)
NO.	NAME	Q'TY	SPECIFICATION

RoHS compliant

Unit: mm

Scale	FREE					Date	Name	Customer-No.
TOLERANCE						Drawn	Winnie	
						Approved	Winnie	ASSMANN WSW-No.
								AK735-5
DIM	TOL	①	Update pin assignment	20.12.2018	Xavier			Drawing-No.
		②	Drawn	24.10.2014	Winnie			ASS 7251 CA
Angle	TOL	Id.	Modification	Date	Name			rev01
								Replace
								Sheet

1

2

3

4

5

6

7