


C440C103G5G5TA

AxiMax 400 Comm COG, Ceramic, 0.01 uF, 2%, 50 VDC, COG, AxiMax, Commercial Standard



General Information Series AxiMax 400 Comm COG Description AxiMax, Commercial Standard RoHS Termination Tin AEC-Q200 No Halogen Free Yes

0.01 uF

1 MHz 1.0 Vrms

Cli

Dimensions	
D	3.81mm MAX
L	6.6mm MAX
LL	25.4mm MIN
F	0.51mm +0.025/-0.076mm

Click here for the 3D model.		Capacitance Folerance	2%
		Voltage DC	50 VDC
		Dielectric Withstanding Voltage	125 VDC
		Temperature Range	-55/+125°C
Dimensions		Temperature Coefficient	COG
D	3.81mm MAX	Capacitance Change with Reference to +25°C	30PPM/C, 1kHz
L	6.6mm MAX	and 0 VDC Applied (TCC)	1.0Vrms
LL	25.4mm MIN	Dissipation Factor	0.1% 1 MHz 1.0Vrms
F	0.51mm +0.025/-0.076mm	Aging Rate	0% Loss/Decade Hour
		Insulation Resistance	100 GOhms

Specifications

Capacitance

Measurement Condition Canaditanaa Talaranaa

Packaging Specifications		
Packaging	Bulk, Bag	
Packaging Quantity	200	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.