

GMA.1B.045.RN

SUMMARY

Wires



Image is for illustrative purpose only

| Series | 1B |
|------------------|-------------------------|
| Termination type | No contacts / Accessory |
| IP rating | 0 |
| AWG wire size | 0.00 - 0.00 |
| Cable Ø | 4.50 - 5.00 mm |
| Status | active |

Download

Request a quote Catalog

TECHNICAL DETAILS

Mechanics

| Shell Style/Model | GMA*: Bend relief Black |
|-----------------------------|-------------------------------------|
| Keying | No keying |
| Housing Material | Silicone elastomer VMQ |
| Variant | N : Black |
| Weight | 1.01 g |
| Housing Material Variant | Silicone elastomer VMQ N : Black |

Performance


Configuration Insulator Rated Current

Others

Temp (min / max): -60°C / +200°C Temperature range in water steam: +140°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

DRAWINGS



No keying

Dimensions

| | А | L |
|-----|------|------|
| mm. | 4.5 | 34 |
| in. | 0,18 | 1,34 |

RECOMMENDED BY LEMO

Tools

Cables

| 120222 | | |
|--------|--|--|
| | | |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.