


- NOTES:
- 10.1" Premium HDMI TFT Module
  - Resolution: 1024x600
  - On-board Analog Devices ADV7611 HDMI Receiver
  - HDMI Audio supported, On-board Texas Instruments TAS5717 Stereo Audio Amplifier
  - On-board L / R Speaker Terminals, supports 24 - 18 AWG wire, suitable for (2) 8Ω speakers up to 10W each
  - Optimal Viewing Direction: Full View
  - Display Mode: Transmissive / Normally White / Anti-Glare
  - Luminance: 800 cd/m<sup>2</sup>
  - 4x Mounting Holes, compatible with Rack Unit (RU) spacing

Improper handling of the FPC connection at the bottom edge of this module may cause damage resulting in display failure. Take special care when handling this area of the display module to make sure this connection is never strained nor creased.

SYMBOL	REVISION	DATE



STANDARD TOLERANCES (UNLESS OTHERWISE SPECIFIED)			
LINEAR: ±0.3 mm	DRAWING/PART NUMBER: <b>NHD-10.1-HDMI-A-RSXV</b>		REVISION: 1.1
UNLESS OTHERWISE SPECIFIED	DRAWN BY: N. Patel	CHECKED BY: P. Bartek	APPROVED BY: M. LaVine
- DIMENSIONS ARE IN MILLIMETERS	DRAWN DATE: 7/31/18	CHECKED DATE: 8/17/18	APPROVED DATE: 8/17/18
- THIRD ANGLE PROJECTION	DO NOT SCALE DRAWING		SHEET 1 OF 1
THIS DRAWING IS SOLELY THE PROPERTY OF NEWHAVEN DISPLAY INTERNATIONAL, INC. THE INFORMATION IT CONTAINS IS NOT TO BE DISCLOSED, REPRODUCED OR COPIED IN WHOLE OR PART WITHOUT WRITTEN APPROVAL FROM NEWHAVEN DISPLAY.			