ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00444	Connector, dc plug, 4.75x1.7xL18.0 mm, molding style, spring contacts, white insulators	1	
2	30-00405	Wire, 2C TS, 24 AWG, UL2468, 300V, 80C, 3.0 mm, VW-1, PVC, 87A, white	1	
3	24-00008	Overmold, PVC, white	1	



Notes:
Cables individually tied and bundled in groups of 10

Functionally equivalent components may be substituted

4 A, 12 Vdc

Wiring Diagram	
50-00544	wire color
center	white with stripe
sleeve	white

Revision:	Date:	Description:
A	11/3/2014	Initial release

Prepared: GL 2016.06.15 14:43:24 -07'00'

Verified: LA

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:

RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:

Cable, 1830 mm, 4.75x1.7x9.5 mm 90° 50-00444 plug to stripped tinned, 24 AWG, 30-00405 wire, white

TENSILITY

tel 1.541.323.3228 *800* 877.670.7118
fax 1.541.323.4202 *web* tensility.com

Size: A

Part number: 10-01250

Scale: 1:2

Sheet 1 of 1

5 4 3 2 1