



LIGHT SOCKETS  
W/ GUARDS  
QTY: 8

**CAUTION-RISK OF SHOCK AND FIRE**  
USE WITH LAMP BASE IN UP POSITION ONLY.  
DISCONNECT PLUG BEFORE RELAMPING OR SERVICING.  
CAUTION - TO REDUCE THE RISK OF ELECTRIC SHOCK AND FIRE, DO NOT EXCEED MARKED LAMPHOLDER WATTAGE OR STRING MAXIMUM WATTAGE INCLUDING ANY ADDITIONAL STRING LOADS.

Assembled in Mexico

**TEMPORARY LIGHTING STRING**  
CAT NO.1301110049 DATE CODE X XXXXXX  
125 VOLT, 15 AMP MAX. 1875W MAX.  
MAX PER SOCKET: 200W TYPE A INCAN.  
OR 35W CFL/LED  
INDOOR USE ONLY

**Woodhead**  
molex

LABEL "A"

**THIS STRINGLIGHT IS INTENDED FOR INDOOR USE ONLY.**  
DO NOT CONNECT OR DISCONNECT WHEN WET. REFER TO PRODUCT INSTRUCTION SHEET FOR APPROPRIATE LAMP TYPES.  
DO NOT USE GE SURVIVOR OR ROUGH SERVICE TYPE LAMPS.

DO NOT EXCEED MARKED SOCKET WATTAGE OR STRING MAX. CURRENT.  
ONLY USE SELF-BALLASTED LAMPS IF A SELF-BALLASTED LAMP TYPE IS IDENTIFIED ON THE TAG.  
FOR USE ONLY ON GFCI PROTECTED CIRCUITS IN ACCORDANCE WITH ARTICLE 590 OF THE NEC.

LABEL "B"

**CAUTION - TO REDUCE THE RISK OF ELECTRIC SHOCK DO NOT CONNECT OR DISCONNECT WHEN WET.**

THIS STRINGLIGHT IS INTENDED FOR INDOOR USE ONLY.  
DO NOT EXCEED 15 AMPS TOTAL STRING CURRENT

LABEL "C"

ITEM	DESCRIPTION	MATERIAL	COLOR
10	OVERMOLD SOCKET	THERMOPLASTIC RUBBER	BLACK
20	CAP	NYLON	BLACK
30	CABLE #12-3 SJTOW RATED AT 300V 60°C	PVC/COPPER	YELLOW
40	HOT CONTACT CENTER	BRASS	PLAIN
50	NEUTRAL CONTACT	BRASS	PLAIN
60	GROUNDING RING	BRASS	PLAIN
70	SCREWSHELL	NYLON	BLACK
80	LAMP GUARD	POLYPROPYLENE	YELLOW

RELEASE SALES DWG EC NO.: IFCG2016-1124 DRWN: HRUIZ01 2016/01/18 CHKD: HKNEELAN 2016/01/18 APPR: JFMURPHY 2016/03/10	QUALITY SYMBOL ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1"> <tr> <td></td> <td>mm</td> <td>INCH</td> </tr> <tr> <td>4 PLACES</td> <td>±---</td> <td>±---</td> </tr> <tr> <td>3 PLACES</td> <td>±---</td> <td>±.005</td> </tr> <tr> <td>2 PLACES</td> <td>±---</td> <td>±.010</td> </tr> <tr> <td>1 PLACE</td> <td>±---</td> <td>±.020</td> </tr> </table>		mm	INCH	4 PLACES	±---	±---	3 PLACES	±---	±.005	2 PLACES	±---	±.010	1 PLACE	±---	±.020	DIMENSION STYLE INCH	SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
		mm	INCH																		
	4 PLACES	±---	±---																		
	3 PLACES	±---	±.005																		
2 PLACES	±---	±.010																			
1 PLACE	±---	±.020																			
		DRAWN BY DATE HRUIZ01 2016/01/18	CHECKED BY DATE HKNEELAN 2016/01/18	TITLE <b>STRINGLIGHT (47.5 FT) #12-3 SJTOW YELLOW CABLE NEMA 5-15P &amp; NEMA L5-15R</b>																	
		APPROVED BY DATE JFMURPHY 2016/03/10	MATERIAL NO. <b>1301110049</b>	DOCUMENT NO. <b>SD-130111-009</b>	SHEET NO. <b>1 OF 1</b>																
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SIZE <b>C</b>	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																	