

Specification Sheet

Part Number: 170-03175



Braided Sleeving, Aluminum Laminated Fiberglass, .38" Dia, AL/GF, Silver, 100 ft/reel

Article Number	170-03175
Type	BSHTTST38SR
Color	Silver (SR)
Features & Benefits	<ul style="list-style-type: none">• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.• Cuts with ordinary scissors for fast, easy application.
Quantity Per	reel

Product Description

High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

Short Description

Braided Sleeving, Aluminum Laminated Fiberglass, .38" Dia, AL/GF, Silver, 100 ft/reel

Global Part Name

BSHTTST38SR-AL/GF-ML

Length L (Imperial)

100.0

Length L (Metric)

30.48

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.54

Bundle Diameter Max (Imperial)

0.437

Bundle Diameter Max (Metric)

11.1

Diameter D (imperial)

0.38

Diameter D (metric)

9.7

Nominal Diameter (Imperial)

3/8

Nominal Diameter (Metric)

9.7

Wall Thickness WT (Imperial)

0.025

Wall Thickness WT (Metric)

0.64

Material

Glass Fiber (GF) Aluminum (AL)

Material Shortcut

GF AL

Flammability

Non-Flammable

Halogen free

Yes

Operating Temperature (Metric)

-76°F to +491°F (-60°C to +255°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

30.48

Customs Number

7019905050

Weight (Metric)

1.1

Weight (Imperial)

2.3

Reel Weight (Imperial)

2.25

Reel Weight (Metric)

1.02