




1





MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V- STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.



			SW REFERENCE NO.: 630 COMBO ASSEMBLY		
COMBINATIO	N D-SUB	DRAWN: C.B	DATE: JAN. 01/20	19	
			DATE:		
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
EDEC INC TORONTO, ONTARIO CANADA		DRAWING NUMBER: 630-2WK2240-3N4 IS		ISSUE	
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-2WK	2240-3N4	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

WITHSTANDING VOLTAGE:

.XX ±0.13

.XXX ±0.05

10:70

5.80

NOTES:

CON OPEF

1000V AC rms

V-0 D

