	T Q T	m	D	0	Ū	A		_
4	R 22.6 Max H H H H H H H H H H H H H H H H H H H	S			T SHOWN AS EXAMPLE			4
	Keying Sh	own as example						
	CHARACTERISTICS Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal						
	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy	A 38.1±0.3 B 23.82+0.1/-0.15 R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1 VV THREAD M18x1-6g		due to a use of tl the Specifications issu	be liable for any non-conformity he Products which does not cor led by either of the Parties or b recommendation, technical no	nply with y a third party		
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum				Country Jurisdi FR	ction & Control List Not Listed]	2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN	: 8D713F98AB			
	-Temperature Range : -65°C to +200°C -Salt Spray : 48 hours		A 28-09-20	16 First Release			J	
	-Mass : 24.18 g ± 10%		ISS DATE Designed By:	Latest modification -	by	CUSTOMER DRAWING	MOD N°	
			TITLE		Aluminium Receptacl			
	BASIC SERIES: 8D 7 - 13 F 98 A	3	SCALE		General linear Tolerances:	NPRDS / PROJECT 859		1
<u> </u>	SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact	ORIENTATION : B	SOURIA	U WWW.SC	± DURIAU.COM	This document is the prop SOURIAU it must not be reproduc	ced or	1
	SHELL SIZE : 13 PLATING : F = Nickel	CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 13-98	FORMAT	S	OURIAU DRG N°	communicated without pe	rmission SHEET	$\left \right $
		7	A3		8D713F98AB-C		1/2	
	H G F	E E	D	C	B	I A		

	I G	m (
	Contact Layout		Panel cutout				
4	$\begin{array}{c} & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & &$		JAM NUT RECEPTACLE (TYPE 7)				
	$\begin{array}{ c c c c c }\hline & & & & & & & & & & & & & & & & & & &$						
ω	J+.065 (1.65)015 (0.38)K065 (1.65)015 (0.38)Shell sizeArrangement no.Number of contactsSize contactsService ratingContact location13981020IAllMS20051-98		Dim Nominal B 24.26+0/-0.25 ØC 25.65+0.25/-0				
			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party				
2			(professional recommendation, technical notice.) Country Jurisdiction & Control List 2 FR Not Listed 2				
			A 28-09-2016 First Release				
			ISS DATE Latest modification - by MOD N° Designed By: Date: CUSTOMER DRAWING				
			TITLE Aluminium Receptacle 8D series SCALE General linear				
→			NA Tolerances: 859				
			SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission communicated without permission				
			FORMATSOURIAU DRG N°SHEETA38D713F98AB-C2/2				
L	H G	F E	D C B A				