

RONDA


Low profile lenses with wide customization possibilities to cover all indoor lighting needs compatible with up to 14 mm LES size COBs and LEDiL HEKLA sockets/connectors.

RONDA is part of LEDiL's platform of modular light engines with very wide customization possibilities. Supporting different base parts and numerous front panel fastening methods it can be adapted to a wide range of applications. Whether used in museums, offices or for architectural purposes the same modular solution can be used with different beam patterns as well. Three holders: Holder A for LEDiL twist and lock base parts + 3rd party connectors (TE, Bender+Wirth, Ideal), Holder B for 3rd party connectors (BJB, Ideal, Stucchi) and Holder C for LEDiL HEKLA.



PRODUCTS:


FN15736_RONDA-WW-B



Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm

~60° wide beam with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi


RONDA-W



Dimensions: 69.9 mm x 69.9 mm Height: 14.00 mm ~45° wide beam with holder A

compatible with 3rd party connectors from TE, Bender+Wirth and IDEAL

RONDA-REC-90-C




Dimensions: 53.9 mm x 53.9 mm Height: 16.60 mm ~80° rectangular beam with holder C compatible with LEDiL HEKLA




PRODUCTS:

RONDA-WWW-C




Dimensions: 53.9 mm x 53.9 mm Height: 17.00 mm ~90° wide beam with holder C compatible with LEDiL HEKLA

RONDA-S-B



Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm ~25° spot beam with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi


RONDA-O-B



Dimensions: 69.9 mm x 69.9 mm Height: 14.50 mm

~50° + 30° oval beam with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi.


RONDA-WW



Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm

~60° wide beam with holder A compatible with 3rd party connectors from TE, Bender+Wirth and IDEAL


RONDA-ZT45-C



Dimensions: 53.9 mm x 53.9 mm Height: 16.60 mm

Double asymmetric beam for wall-washing and aisle lighting with holder C compatible with LEDiL HEKLA

RONDA-REC-90




Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm

~80°+80° rectangular beam with holder A compatible with 3rd party connectors from TE, Bender+Wirth and IDEAL



PRODUCTS:


RONDA-WAS-B



Dimensions: 69.9 mm x 69.9 mm Height: 22.30 mm

Asymmetric beam for wall washing with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi


RONDA-WAS2-B



Dimensions: 69.9 mm x 69.9 mm Height: 14.50 mm

Asymmetric beam for wall-washing with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi.


RONDA-WAS



Dimensions: 69.9 mm x 69.9 mm Height: 21.80 mm Asymmetric beam for wall washing


with holder A compatible with 3rd party connectors from TE, Bender+Wirth and IDEAL

RONDA-S-C




Dimensions: 52.1 mm x 52.1 mm Height: 17.20 mm ~25° spot beam with holder C compatible with LEDiL HEKLA

RONDA-WWW-B



Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm ~90° very wide beam with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi.

RONDA-REC-60




Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm

~60° + 60° rectangular beam with holder A compatible with 3rd party connectors from TE, Bender+Wirth and IDEAL




PRODUCTS:

RONDA-WAS2-C




Dimensions: 53.9 mm x 53.9 mm Height: 16.00 mm Asymmetric beam ideal for floor installations with holder C compatible with LEDiL HEKLA

RONDA-WW-C




Dimensions: 53.9 mm x 53.9 mm Height: 16.90 mm ~60° wide beam with holder C compatible with LEDiL HEKLA

RONDA-W-B



Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm ~45° wide beam with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi


RONDA-O-C



Dimensions: 53.9 mm x 53.9 mm Height: 20.50 mm $50^{\circ} + 30^{\circ}$ oval beam with holder C

~50° + 30° oval beam with holder C compatible with LEDiL HEKLA


RONDA-ZT45



Dimensions: 69.9 mm x 69.9 mm Height: 15.00 mm

Double asymmetric beam for wall-washing and aisle lighting with holder A compatible with 3rd party connectors from TE, Bender+Wirth and IDEAL

RONDA-REC-60-C




Dimensions: 53.9 mm x 53.9 mm Height: 16.60 mm ~60° + 60° rectangular beam with holder C compatible with LEDiL HEKLA



PRODUCTS:


RONDA-REC-90-B



Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm

~80°+80° rectangular beam with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi


RONDA-ZT45-B



Dimensions: 69.9 mm x 69.9 mm Height: 15.40 mm

Double asymmetric beam for wall-washing and aisle lighting with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi


RONDA-O



Dimensions: 69.9 mm x 69.9 mm Height: 17.28 mm

~50° + 30° oval beam with holder A compatible with 3rd party connectors from TE, Bender+Wirth and IDEAL.


RONDA-WWW



Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm


~90° very wide beam with holder A compatible with 3rd party connectors from TE, Bender+Wirth and IDEAL

RONDA-WAS-C



Dimensions: 53.9 mm x 53.9 mm Height: 24.65 mm Asymmetric beam for wall washing with holder C compatible with LEDiL HEKLA

RONDA-REC-60-B




Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm

~60° + 60° rectangular beam with holder B compatible with 3rd party connectors from BJB, IDEAL and Stucchi



PRODUCTS:


RONDA-S



Dimensions: 69.9 mm x 69.9 mm Height: 17.20 mm

~25° spot beam with holder A compatible with 3rd party connectors from TE, Bender+Wirth and IDEAL


RONDA-WAS2



Dimensions: 69.9 mm x 69.9 mm Height: 14.60 mm

Asymmetric beam for wall-washing with holder A compatible with TE, Bender+Wirth and IDEAL

RONDA-W-C



Dimensions: 52.1 mm x 52.1 mm Height: 16.98 mm ~45° wide beam with holder C compatible with LEDiL HEKLA



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy