© Co	terial Composition pyright 2005. IPC, Banational and Pan-Ame	annockbu	ırn, Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a decla he declaratio	aration of the second s	of the substation of the subst	nces wi lower le	thin the manufa evel materials fo	cturer listed r which the	item. I manufa	Note: if tl acturer h	he item is an as as engineering	sembly with lowe responsibility.	
					Form Type Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					terials and N	als and Mfg Information				
Supplier Information																	
Company name*			Company unique ID			Unique ID Authority					Respor	Response Date*					
onsemi												2023-0	2023-06-08				
Contact Name			Title - Contact]	Phone - Contact*					Email	Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance				NA					Produ	Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative			Phone - Representative*				Email	Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com						
Requester Item N	lester Item Number Mfr Iter		n Number Mfr Item Name				Effective Dat		Version	Ma	Manufacturing Site		Weigl	nt*	UOM	Unit Type	
	NLAS5223CLMUT G			A LOW VOLTAGE DUAL SPDT ANALOG SWITCH			2023-06-08	3		М	MY1		3.54		mg	Each	
Manufacturing Procee	ess Information									·							
Terminal Plating	nal Plating / Grid Array Material Terr		rminal Base A	ase Alloy J-STD-020 MSL I		Rating	Peak Process Body		Body Tempe	Temperature Max Time at Peak		eak Tempera	Temperature Numbe		of Reflow Cyc	les	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		(no CU	U Alloy 1		1		260		С		30 sec		nds	3			
Comments																	
evel 1 - maximum time at p	eak temperature du	ring sold	lering is 10-3	0 seconds													
or more information rega	rding material comp	osition p	lease refer to	page 3													

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless								
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.24	mg	Supplier	Silicon (Si)	7440-21-3		0.24	mg
Die Attach	0.1	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.032	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.068	mg
Lead Frame	0.59	mg	Supplier	Silver (Ag)	7440-22-4		0.0118	mg
			Supplier	Iron (Fe)	7439-89-6		0.013	mg
			Supplier	Copper (Cu)	7440-50-8		0.5652	mg
Mold Compound-Black	2.49	mg		Epoxy Phenol Resin	proprietary data		0.2241	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		2.2659	mg
Plating	0.01	mg	Supplier	Palladium (Pd)	7440-05-3		0.0003	mg
			В	Nickel (Ni)	7440-02-0		0.0096	mg
			Supplier	Gold (Au)	7440-57-5		0.0001	mg
Wire Bond - Au	0.11	mg	Supplier	Gold (Au)	7440-57-5		0.11	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).