


10HV36N823JC

HV RAD-LDD Indust COG HV, Ceramic, 0.082 uF, 5%, 1000 VDC, COG, Commercial, High Voltage, Lead Spacing = 34.92mm



Click here for the 3D model.

Dimensions	
L	36.83mm MAX
Н	18.29mm MAX
Т	6.89mm MAX
S	34.92mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

Packaging Specifications			
Packaging	Waffle		
Packaging Quantity	4		

General Information			
Series	HV RAD-LDD Indust COG HV		
Style	Radial		
Description	Commercial, High Voltage		
Features	Commercial		
RoHS	No		
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.		
SCIP Number	ef26097b-3862-4ee0-b0ad-404a563ece0f		
Termination	Copper		
Failure Rate	N/A		
AEC-Q200	No		

Specifications				
Capacitance	0.082 uF			
Capacitance Tolerance	5%			
Voltage DC	1000 VDC			
Dielectric Withstanding Voltage	1200 VDC			
Temperature Range	-55/+125°C			
Temperature Coefficient	COG			
Dissipation Factor	0.15%			
Aging Rate	0% Loss/Decade Hour			
Insulation Resistance	12.1951 GOhms			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.