Г	T	G	-	Π	m			C
4	R 22.6 Max	N Thread						
			к	eying Shown as	example			
2	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 -Shell Material : Stainless Sta -Shell Plating : Nickel -Insulator : Thermoplas -Contacts : Copper Allo -Seals & Grommet : Silicon Elast	eel stic yy tomer			Connector dimension Dim Nominal A 38.1±0.3 B 23.82+0.1/-0.15 R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1 VV THREAD M18x1-6g			SOURIAU sha due to a us the Specificatio (profes
	-Contact Plating: Gold over c-Durability: 500 Mating-Delivered with Souriau contacts and-Temperature Range: -65°C to +2-Salt Spray: 500 hours	Accessories	m				ISS DATE	First Release Latest modifica
_ _	BASIC SERIES: SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Co	8D 7 - 13	S 98	B D	ORIF	NTATION : D	Designed By: TITLE SCALE NA	
	SHELL SIZE : 13				CONTACT TYPE : SOCKET(5		SOURIAU	WWV
	PLATING : S = Nickel				CONTACT LAY	OUT : 13-98	FORMAT A3	1

G F

L_____

Н

	A	28-09-2016		First Release			
	ISS	DA	ΛTE	Latest modifica			
	Design	ied By:		Date			
		TITLE	:				
		ALE A	-				
: D	SOURIAU			WWW			
ngs)							
-98	FOR	MAT		1			
	A	3					
	D			С			

 $\backslash /$

Е

B						
	4					
LAYOUT SHOWN AS EXAMPLE	3					
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party essional recommendation, technical notice.) <u>Country</u> Jurisdiction & Control List FR Not Listed PN: 8D713S98BD						
ation - by MOD N° te: CUSTOMER DRAWING Stainless Steel Receptacle 8D series						
General linear NPRDS / PROJECT Tolerances: 859						
W.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
SOURIAU DRG N° SHEET						
8D713S98BD-C 1/2						

ſ	I	Q	П	т		0	σ	1	>	,
	Cor	ntact Layout				Panel cutout				
4	⊕°),×.	$ \begin{array}{c} & & & & \\ & & & \\ & & & \\ & & & \\ $				JAM NUT RECEPTACLE (TYPE 7)				4
	B C D E F G H	Location X-axis (mm) Y-axis (mm) +.000 (0.00) +.195 (4.95) +.125 (3.18) +.150 (3.81) +.133 (4.90) +.030 (0.76) +.104 (4.17) 105 (2.07) +.000 (0.00) 135 (3.43) 164 (4.17) 105 (2.67) 193 (4.90) +.030 (0.76) 125 (3.18) +.150 (3.81)				ØC				
ω		contacts rating location				DimNominalB24.26+0/-0.25ØC25.65+0.25/-0				3
	_									
						SOURIAU shall not be liable for a due to a use of the Products the Specifications issued by either (professional recommend	which does not com of the Parties or by	oly with a third party		
N						CountryJurisdiction & Control ListFRNot Listed				2
					PN: 8D713S98BD					
					A 28-09-2 ISS DATE	016 First Release			MOD N°	_
					Designed By:	Date:		CUSTOMER DRAWING		-
					TITLE	Stainless S	teel Receptac	e 8D series		
_					SCALE NA	General linear Tolerances:	-	NPRDS / PROJECT 859		1
					SOURIA	WWW.SOURIAU	.COM	This document is the p SOURIAU it must not be repro communicated without	duced or	
				I	FORMAT A3		U DRG N° 598BD-C		SHEET 2/2	
L	Н	G	F	E	D	C	В	ļ	A	J