



Issue Date: September 09 2013

		_	
HS CABLE ASSEMBLIES			
Mini SAS Cable Assy			
Jerry YI			
Notification of Change with Immediate Effectivity			
Global			
Materials Change			
Change material of the EMI gasket to a stronger tensile-strength and modify the design from a solid structure to a hollow-type structure. These changes are also incorporated with a supplier change for the EMI gasket.			
This is a quality improvement intended to prevent easy breakage of the EMI gasket which has been reported by some customers.			
See attachment			
September	15	2013	
N/A	N/A	N/A	
N/A	N/A	N/A	
N/A	N/A	N/A	
N/A			
N/A			
September	09	2013	
N/A			
Contact your local FCI Representative, or Product Marketing Manager			
Jerry YI/ Product manager			
Phone number: 86 513 80167339 / e-mail address:Jerry.Yi@fci.com			
1 . 1	Mini SAS Ca Jerry YI Notification of Global Materials Ch Change mate to a hollow-ty This is a qua by some cus See attachm September N/A N/A N/A N/A N/A N/A September N/A Contact your Jerry YI/ Pro	Mini SAS Cable Assy Jerry YI Notification of Change Global Materials Change Change material of the content o	Mini SAS Cable Assy Jerry YI Notification of Change with Immediate Solution of Change with Immediate Solution of Change with Immediate Solution and Solution of Change Materials Change Change material of the EMI gasle to a hollow-type structure. These solution of the EMI gasle to a hollow-type structure of the EMI gasle to a hollow-type structure. These solution of the EMI gasle to a hollow-type structure. These solution of the EMI gasle to a hollow-type structure. These solution of the EMI gasle to a hollow-type structure. These solution of the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the solution of the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. These solutions is a quality improvement into the EMI gasle to a hollow-type structure. The emit gasle to a hollow-type structure. The emit gasle to a hollow-type structure. The emit gasle to a hollow-type