


COMPLIANT


NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED
OPERATING TEMPERATURE:	-55°C ~ 125°C
POWER/CO-AX CONTACT RATING: (IF PRESENT)	10A (CURRENT)
SIGNAL CONTACT CURRENT RATING:	
INSULATOR RESISTANCE:	5000MΩ min.
DIELECTRIC WITHSTANDING VOLTAGE:	1000V AC rms

SW REFERENCE NO .: 630 COMBO ASSEMBLY COMBINATION D-SUB DATE: JAN. 01/2019 DRAWN: C.B CHECKED: DATE: THESE DRAWINGS AND SPECIFICATIONS (IN C.A.D. 1:1) OF 2 SCALE: SHEET 1 EDAC INC ARE THE PROPERTY OF EDAC INC. AND TORONTO, ONTARIO SHALL NOT BE REPRODUCED, OR COPIED 630-3WK3240-1N5 ISSUE DRAWING NUMBER: OR USED AS THE BASIS FOR THE CANADA MANUFACTURE OR SALE OF APPARATUS 1 YOUR CONNECTION TO QUALITY & SERVICE PART NUMBER: 630-3WK3240-1N5 WITHOUT WRITTEN PERMISSION.







.XX

±0.13

.XXX ±0.05

