ATGBICS LC-LC OM4, Fibre Optic Cable, Multimode, Duplex, Aqua, 20m

Brand : ATGBICS

Product code: CAB-OM4-LC-LC-20M-D

Product name : LC-LC OM4, ATGBICS Fibre Optic Cable, Multimode, Duplex, Aqua, 20m

LC-LC OM4, ATGBICS Fibre Optic Cable, Multimode, Duplex, Aqua, 20m

ATGBICS LC-LC OM4, Fibre Optic Cable, Multimode, Duplex, Aqua, 20m:

This product is high quality LC-LC (male to male) Fibre Patch Cable. LC connections allow higher density applications based on its smaller diameter. The OM4 cable type has a higher attenuation that helps reduce losses over greater distances. It supports 10 Gigabit Ethernet at lengths measuring up to 550 meters, with 40 Gigabit and 100 Gigabit Ethernet measuring up to 150 meters. depending on the type of transceiver and wavelength. The OM4 cable has a core size of 50 microns and the diameter of the outer cladding is 125 microns.


ATGBICS LC-LC OM4, Fibre Optic Cable, Multimode, Duplex, Aqua, 20m. Cable length: 20 m, Cable type: OFNR, Fibre optic type: OM4, Connector 1: LC, Connector 2: LC, Core diameter: 50 μm, Full duplex





Cable length *20 mEthernet interface type10 Gigabit Ethernet, 40 Gigabit Ethernet, 100 Gigabit EthernetConnector 1 *LCInsertion loss0.2 dBConnector 1 gender *MaleReturn loss50 dBConnector 2 gender *MaleJacket material *Polyvinyl chloride (PVC)Connector 2 gender *MaleCountry of originChinaConnector polish typeUPCCountry of originChinaCable type *OFNRTechnical detailsReturn lossFibre optic type *OM4Sustainability certificatesRoHSProduct colour *Aqua colourDoesn't containHalogenFull duplex✓Operating temperature (T-T)-40 - 70 °CCadding diameter125 µmOperating temperature (T-T)-40 - 70 °CFiber mode structureMulti-modeStorage temperature (T-T)-40 - 70 °CWavelengths supported850,1300 nmWeight & dimensionsZ	Features		Features	
Cable type *OFNRTechnical detailsFibre optic type *OM4Sustainability certificatesRoHSProduct colour *Aqua colourDoesn't containHalogenFull duplex✓Operational conditionsCore diameter50 μmCladding diameter125 μmOperating temperature (T-T)-40 - 70 °CFiber mode structureMulti-modeStorage temperature (T-T)-40 - 70 °CWavelengths supported850,1300 nmWeight & dimensionsCable diameter2 mm	Connector 1 *LCConnector 2 *LCConnector 1 gender *MaleConnector 2 gender *MaleConnector polish typeUPCCable type *OFNRFibre optic type *OM4	LC LC Male Male	Insertion loss Return loss Jacket material *	Ethernet, 100 Gigabit Ethernet 0.2 dB 50 dB Polyvinyl chloride (PVC)
Core diameter 50 μm Operational conditions Cladding diameter 125 μm Operating temperature (T-T) -40 - 70 °C Fiber mode structure Multi-mode Storage temperature (T-T) -40 - 70 °C Wavelengths supported 850,1300 nm Weight & dimensions -40 - 70 °C		Sustainability certificates		
Cable diameter 2 mm	Core diameter Cladding diameter	Core diameter 50 μm Cladding diameter 125 μm Fiber mode structure Multi-mode	Operating temperature (T-T)	
	Wavelengths supported		-	2 mm

Quantity per pack 1 pc(s)



5056468735607

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.