




SPX-8-6-SS

Ruland SPX-8-6-SS, 1/2" x 3/8" Rigid Coupling, 303 Stainless Steel, Two-Piece Clamp Style, 1 1/8" OD, 1 3/4" Length




Description

Ruland SPX-8-6-SS is a two-piece rigid coupling with 0.5000" x 0.3750" bores, 1 1/8" OD, and 1 3/4" length. SPX-8-6-SS has opposing hardware for a balanced design. Proprietary Nypatch® anti-vibration coating on hardware allows for even seating of the screw, repeated screw installations, prevents galling, and maintains high holding power. It eliminates the need to treat screws upon receipt greatly reducing installation time. Forged screws test beyond ANSI standards to ensure maximum holding power. Tightly controlled bore tolerance of +.002"/+.0005" is maintained. SPX-8-6-SS is made from 303 stainless steel with hardware of like material for consistent corrosion resistance. It is machined from solid bar stock that is sourced exclusively from North American mills and is RoHS3 and REACH compliant. SPX-8-6-SS is manufactured in our Marlborough, MA factory under strict controls using proprietary processes.

Product Specifications

Bore (B1)	0.5000 in	Small Bore (B2)	0.3750 in
B1 Max Shaft Penetration	0.875 in	B2 Max Shaft Penetration	0.875 in
Outer Diameter (OD)	1 1/8 in	Bore Tolerance	+0.0020 in / +0.0005 in
Length (L)	1 3/4 in	Clearance Diameter (C) MAX	1.328 in
Recommended Gap	0.063 in	Recommended Shaft Tolerance	+0.0000 in / -0.0005 in
Forged Clamp Screw	#8-32	Screw Material	18-8 300 Series Stainless Steel with Nypatch®
Hex Wrench Size	9/64 in	Screw Finish	Bright
Seating Torque	28 lb-in	Screw Location (R)	0.430 in
Number of Screws	8 ea	Rated Torque	275 in-lb
Moment of Inertia	0.0709 lb-in ²	Maximum Speed	4,000 RPM
Full Bearing Support Required?	No	Nypatch® Anti-Vibration Hardware?	Yes
Zero-Backlash?	Yes	Balanced Design	Yes
Material Specification	Type 303 Austenitic, Non-Magnetic Bar	Temperature	-40°F to 350°F (-40°C to 176°C)
Finish Specification	Bright, No Plating	Manufacturer	Ruland Manufacturing
Country of Origin	USA	Weight (lbs)	0.385000
UPC	634529026502	Tariff Code	8483.60.8000
UNSPC	31163009		

Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.

Prop 65  **WARNING** This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Installation Instructions

1. Align the SPX-8-6-SS two-piece rigid coupling on the two shafts to be connected. There should be no misalignment.
2. Tighten the Nypatch® screws in two stages, starting with the inside screws. Using a 9/64 in torque wrench, tighten the inside screws to 14 lb-in which is half the recommended seating torque. Repeat the process for the outside screws, tightening to half the recommended seating torque.
3. Be sure to maintain the gap of 0.063 in between the two halves during installation.
4. Tighten the screws to the full recommended seating torque of 28 lb-in following the same pattern, starting with the inside screws first.
5. For optimum results do not exceed the shaft penetration length of 0.875 in.

