



- NOTES:
- MATERIAL:  
HOUSING: LCP G.F. UL94 V-0, COLOUR BLACK.  
TERMINAL: PHOSPHUR BRONZE PLATED WITH 0.00005 MIN GOLD FLASH, OVER 0.0010 MIN PALLADIUM NICKEL IN CONTACT AREA, BOTH OVER 0.00127 MIN NICKEL OVERALL.
  - JACK FOR MATING WITH IEC 60603-7 & TIA 1096 PLUGS (95043 MOLEX SERIES)
  - PRODUCT SPECIFICATION: PS-85508-0001
  - PACKAGING SPECIFICATION: T.B.D.
  - COPLANARITY OF SIGNAL LEADS: 0.10MAX
  - EXCEEDS CATEGORY 5E PERFORMANCE
  - RECOMMENDED PCB THICKNESS 1.57

LAST INSPECTION NUMBER USED: 13

MOD SOLDER TAILS	EC NO: IPG2013-1552	2013/04/08
DRW:DBYRNES	2013/05/10	
CHKD:DMAHER	2013/06/05	
APPR:STGRIFFIN		

QUALITY SYMBOLS	DESCRIPTION
▽=0	
∇=0	

GENERAL TOLERANCES (UNLESS SPECIFIED)	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± 0.15	± ---
1 PLACE	± 0.25	± ---
ANGULAR ± 2 °		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		

DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
MM ONLY		5:1	METRIC	☉
DRAWN BY	DATE	TITLE		
DBYRNES	2012/02/23	CAT5E TOP ENTRY SHIELDED SMT		
CHECKED BY	DATE			
DMAHER				
APPROVED BY	DATE			
STGRIFFIN	2012/10/26			
MATERIAL NO.				
93326-0001				

MOLEX INCORPORATED		SHEET NO.
DOCUMENT NO.		1 OF 1
SD-93326-001		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		